

## DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011  
(Construction Products Regulation)

### Nr. DoP-DE-xerm 847

- Unique identification code of the product-type:*  
**weber.xerm 847**  
R2 TE according to DIN EN 12004
- Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*  
Batch/production date/production site/serial No. is printed on packaging or accompanying documents
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*  
Improved highly deformable reaction resin adhesive with reduced slip and extended open time for internal and external tiling
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*  
Saint-Gobain Weber GmbH  
Schanzenstr. 84  
D-40549 Düsseldorf  
[www.sg-weber.de](http://www.sg-weber.de)
- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*  
not applicable
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*  
AVCP System 3
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:*  
The notified testing laboratory Materialprüfanstalt Nordrhein-Westfalen, identification number No. 0432, performed the determination of the product-type on the basis of type testing under system 3 and issued: test report No. 220007395-09-38.
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*  
not applicable

9. Declared performance

Essential characteristic	Performance	Harmonised technical specification
Reaction to fire	Class E	DIN EN 12004:2012-09
Initial shear adhesion strength	$\geq 2,0 \text{ N/mm}^2$	
Shear adhesion strength after thermal shock	$\geq 2,0 \text{ N/mm}^2$	
Shear adhesion after water immersion	$\geq 2,0 \text{ N/mm}^2$	
Release of dangerous substances	NPD	

NPD (No Performance Determined)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Bruno Reisch, Direktor Technik

Düsseldorf, ..... July 11, 2013 .....  
 (Place and date of issue)

..... ppa Reisch .....  
 (Signature)

Annex  
 Material safety data sheet weber.xerm 847