

Printing date 15.03.2021 Version number 1 Revision: 15.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weber TopDry Primer

Safety data sheet no.: 358P0281

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Construction chemicals

Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 295

e-mail: info@fi.weber www.fi.weber

1.4 Emergency telephone number:

+358 800 147 111 +358 9 471 977

Finnish Poison Information Centre

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Additional information:

Information according to regulation (EU) 528/2012: contains

Active substance for preservation during storage: reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1) (CAS no.: 55965-84-9)

EUH208 Contains reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Acrylate dispersion

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Revision: 15.03.2021 Printing date 15.03.2021 Version number 1

Trade name weber TopDry Primer

		(Contd. of pag
Dangerous components:		
CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	10-20%
CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6 Reg.nr.: 01-2120761540-60- xxxx	1,2-benzisothiazol-3(2H)-one Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	<0.05%
CAS: 55965-84-9 EC number: 611-341-5 Index number: 613-167-00-5 Reg.nr.: 01-2120764691-48- xxxx	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)	≥0.00025-<0.0015

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Immediately remove any clothing soiled by the product.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Drink plenty of water and provide fresh air. Call for a doctor immediately.

Information for doctor None

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Use fire extinguishing methods suitable to surrounding

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 15.03.2021 Version number 1 Revision: 15.03.2021

Trade name weber TopDry Primer

(Contd. of page 2)

5.3 Advice for firefighters

Protective equipment: Use methods suitable to surrounding conditions.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Dispose of the material collected according to regulations.

6.4 Reference to other sections See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from freezing.

Recommended storage temperature: 5-30°C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS No. Designat	CAS No. Designation of material % Type Value Unit			
CAS: 14808-60-7 Sili	CAS: 14808-60-7 Silicon dioxide (Quartz sand)			
BOELV (European Union) Long-term value: 0.1* mg/m³ *respirable fraction				
MAK (Germany)	alveolengängige Fraktion	alveolengängige Fraktion		
GV (Denmark)	Long-term value: 0.3* 0.1** mg/m³ *total:,**total, respirabel, EK			
LEP (Spain)	Long-term value: 0.05 mg/m³ *Fracción resp:n,d,y			
TWA (Italy)	Long-term value: 0.025 mg/m³ A2, (j)			
VLE (Portugal)	Long-term value: 0.025 mg/m³ Resp.;A2; fibrose pulmonar; cancro do pulmão			
	·	(Contd. on page 4)		



according to 1907/2006/EC, Article 31

Printing date 15.03.2021 Version number 1 Revision: 15.03.2021

Trade name weber TopDry Primer

(Contd. of page 3) Long-term value: 0.1 mg/m³ OEL (Sweden) C, M, respirabel fraktion Long-term value: 0.05 0.1* mg/m3 HTP (Finland) alveolijae;*sitovat raja-arvot, pöly

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing.

Respiratory protection: Not necessary if room is well-ventilated.

Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: ≥ (Butyl) 0.7 mm; (NBR) 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Breakthrough time: > 480 min

Value for the permeation: Level < 6

The exact breaktrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties **General Information** Appearance: Form: Pasty Colour: According to product specification Odour: Characteristic Odour threshold: Not determined. pH-value at 20 °C: 9.0 (DIN 19261) Change in condition Melting point/freezing point: 0 °C (DIN ISO 3016) Initial boiling point and boiling range: 100 °C (DIN) Flash point: Not applicable Ignition temperature: Not determined.



Printing date 15.03.2021 Version number 1 Revision: 15.03.2021

Trade name weber TopDry Primer

	(Contd. of page
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Oxidising properties	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	1.45 g/cm³ (DIN 51757)
Bulk density:	Not applicable.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible
Segregation coefficient (n-octanol/w	vater) log
Pow:	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Solvent separation test:	Not applicable.
Solvent content:	
Organic solvents:	0.0 %
EU-VOC (%)	0.10 %
EU-VOC (g/L)	2.3 g/l
9.2 Other information	None.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species	
CAS: 1317-65-3 limes	stone			
Oral LD50 >5,000 m	g/kg (Rat)			

(Contd. on page 6)



Printing date 15.03.2021 Version number 1 Revision: 15.03.2021

Trade name weber TopDry Primer

(Contd. of page 5)

aqueous dispersion of a copolymer based on styrene and acrylic acid ester

Oral LD50 >2,000-10,000 mg/kg (Rat)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction to already sensitised individuals (supplemental labelling EUH208 in Europe)

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

CAS: 1317-65-3 limestone

LC50/96h |>10,000 mg/l (Oncorhynchus mykiss (Rainbow trout))

EC50/48h >1,000 mg/l (Daphnia magna)

EC50/72h >200 mg/l (Algae)

aqueous dispersion of a copolymer based on styrene and acrylic acid ester

LC50/96h >100 mg/l (Brachydanio rerio (zebra danio))

12.2 Persistence and degradability No further relevant information available.

Other information: The product is not easily biodegradable.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark: The product contains substances which causes severe clouding in water

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

After prior treatment product has to be landfilled adhering to the regulations pertaining to the disposal of particularly hazardous waste.

(Contd. on page 7)



Printing date 15.03.2021 Version number 1 Revision: 15.03.2021

Trade name weber TopDry Primer

European waste catalogue

(Contd. of page 6)

Possible waste code. The concrete waste code depends on the source of the waste.

08 01 20 aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled

after thorough and proper cleaning.

Recommended cleaning agent: Water, if necessary together with cleansing agents.

SECTION 14: Transport informatio	n	
14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.		
Transport/Additional information:	Not dangerous according to the above specifications.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/CE (VOC), cf. section 9

Regulation (EU) 528/2012 (Biocidal Product Regulation), cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 15.03.2021 Version number 1 Revision: 15.03.2021

Trade name weber TopDry Primer

(Contd. of page 7)

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Department issuing SDS:

Saint-Gobain Finland Oy / Weber

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 520

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1