

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2021

Version number 1

Revision: 28.10.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **weber JB 600/3 P Non-shrink grout frost C50/60-4**

Safety data sheet no.: 358P0641

UFI: W5C6-M3YU-MA9A-A2HA

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

**Application of the substance / the mixture** Construction chemicals

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 295

e-mail: info@fi.weber

www.fi.weber

#### 1.4 Emergency telephone number:

+358 800 147 111

+358 9 471 977

Finnish Poison Information Centre

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

---

#### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms



GHS05 GHS07

**Signal word** Danger

##### Hazard-determining components of labelling:

cement portland, grey

##### Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

(Contd. on page 2)

EUG

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2021

Version number 1

Revision: 28.10.2021

**Trade name weber JB 600/3 P Non-shrink grout frost C50/60-4**

(Contd. of page 1)

**Precautionary statements**

P102 Keep out of reach of children.  
 P261 Avoid breathing dust.  
 P280 Wear protective gloves / eye protection / face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/doctor.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards**

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

**Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

**Description:** Ready-mixed mortar with Portland cement

<b>Dangerous components:</b>		
CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	50-75%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	25-50%
CAS: 7631-99-4 EINECS: 231-554-3 Reg.nr.: 01-2119488221-41-xxxx	sodium nitrate ⚠ Ox. Sol. 2, H272; ⚠ Eye Irrit. 2, H319	1-2%

**SVHC** Void

**Additional information**

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**

**After inhalation** Supply fresh air and to be sure call for a doctor.

**After skin contact** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2021

Version number 1

Revision: 28.10.2021

**Trade name weber JB 600/3 P Non-shrink grout frost C50/60-4**

(Contd. of page 2)

**After eye contact**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

**After swallowing**

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

**4.2 Most important symptoms and effects, both acute and delayed**

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media****Suitable extinguishing agents**

The product is not combustible.

Use fire extinguishing methods suitable to surrounding conditions.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

**5.3 Advice for firefighters**

**Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective clothing.

**6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.

**6.3 Methods and material for containment and cleaning up:**

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

**7.1 Precautions for safe handling**

Prevent formation of dust.

Provide suction extractors if dust is formed.

**Information about fire - and explosion protection:** No special measures required.

**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Store in dry conditions.

(Contd. on page 4)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2021

Version number 1

Revision: 28.10.2021

**Trade name weber JB 600/3 P Non-shrink grout frost C50/60-4**

(Contd. of page 3)

**7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

**Ingredients with limit values that require monitoring at the workplace:**

CAS No.	Designation of material	%	Type	Value	Unit
<b>CAS: 14808-60-7 Silicon dioxide (Quartz sand)</b>					
BOELV (European Union)	Long-term value: 0.1* mg/m <sup>3</sup> *respirable fraction				
MAK (Germany)	Long-term value: 0.05 mg/m <sup>3</sup> alveolengängige Fraktion				
GV (Denmark)	Long-term value: 0.3* 0.1** mg/m <sup>3</sup> *total, **total, respirabel, EK				
LEP (Spain)	Long-term value: 0.05 mg/m <sup>3</sup> *Fracción resp:n,d,y				
TWA (Italy)	Long-term value: 0.025 mg/m <sup>3</sup> A2, (j)				
VLE (Portugal)	Long-term value: 0.025 mg/m <sup>3</sup> Resp.;A2; fibrose pulmonar; cancro do pulmão				
OEL (Sweden)	Long-term value: 0.1 mg/m <sup>3</sup> C, M, respirabel fraktion				
HTP (Finland)	Long-term value: 0.05 0.1* mg/m <sup>3</sup> alveolijae;*sitovat raja-arvot, pöly				
<b>CAS: 65997-15-1 cement portland, grey</b>					
AGW (Germany)	Long-term value: 5 E mg/m <sup>3</sup> DFG				
LEP (Spain)	Long-term value: 4 mg/m <sup>3</sup> fracción respirable: e, d				
TWA (Italy)	Long-term value: 1 mg/m <sup>3</sup> (e, j), A4				
VLE (Portugal)	Long-term value: 1 mg/m <sup>3</sup> Fração resp.;A4,função pulm.,sintomas resp.,asma				
HTP (Finland)	Long-term value: 5* 1** mg/m <sup>3</sup> *hengittyvä pöly, **alveolijae				

#### 8.2 Exposure controls

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

**Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter P3.

(Contd. on page 5)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.10.2021

Version number 1

Revision: 28.10.2021

**Trade name weber JB 600/3 P Non-shrink grout frost C50/60-4**

(Contd. of page 4)

**Hand protection**

Protective gloves.

The hands must be cleaned from the powder before putting on the gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

**Eye/face protection** Safety glasses.

**Body protection:** Protective work clothing.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Colour:** According to product specification

**Odour:** Specific type

**Odour threshold:** Not determined.

**Melting point/freezing point:** Undetermined.

**Boiling point or initial boiling point and boiling range** Undetermined.

**Flammability** Product is not flammable.

**Lower and upper explosion limit**

**Lower:** Not determined.

**Upper:** Not determined.

**Flash point:** Not applicable

**Decomposition temperature:** Not determined.

**pH** 12-13  
In water

**Viscosity:**

**Kinematic viscosity** Not determined.

**dynamic:** Not determined.

**Solubility**

**Water:** Miscible

**Partition coefficient n-octanol/water (log value)** Not determined.

**Vapour pressure:** Not determined.

Not applicable.

**Density and/or relative density**

**Density:** 1.5-1.7 g/cm<sup>3</sup>

**Vapour density** Not applicable.

**Particle characteristics** See item 3.

**9.2 Other information**

No further relevant information available.

**Appearance:**

**Form:** Powder

**Important information on protection of health and environment, and on safety.**

**Ignition temperature:** Not determined.

**Explosive properties:** Product does not present an explosion hazard.

**Minimum ignition energy**

**Solvent content:**

**Organic solvents:** 0.0 %

**EU-VOC (g/L)**

**Solids content:** 100.0 %

(Contd. on page 6)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2021

Version number 1

Revision: 28.10.2021

**Trade name weber JB 600/3 P Non-shrink grout frost C50/60-4**

(Contd. of page 5)

<b>Change in condition</b>	
<b>Softening point/range</b>	
<b>Oxidising properties</b>	Not determined.
<b>Evaporation rate</b>	Not applicable.

**Information with regard to physical hazard classes**

<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Void
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- 10.1 Reactivity** When mixed with water the product hardens forming a stable non-reactive mass.
- 10.2 Chemical stability** Stable at recommended storage conditions
- 10.3 Possibility of hazardous reactions** No dangerous reactions known
- 10.4 Conditions to avoid**  
Avoid water ingress/moisture during storage (the product will react with moisture and harden).
- 10.5 Incompatible materials:** Acids, ammonium salts, aluminum, non-precious metals.
- 10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

Components	Type	Value	Species
<b>CAS: 65997-15-1 cement portland, grey</b>			
Dermal	LD50	>2,000 mg/kg	(Rabbit)

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation**

Causes serious eye damage.

(Contd. on page 7)

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2021

Version number 1

Revision: 28.10.2021

**Trade name weber JB 600/3 P Non-shrink grout frost C50/60-4**

(Contd. of page 6)

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

**12.1 Toxicity**

**Aquatic toxicity:** Not classified as harmful to aquatic life

**12.2 Persistence and degradability** The product is not biodegradable.

**12.3 Bioaccumulative potential** Does not accumulate in organisms

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects** No further relevant information available.

**Remark:**

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

**Additional ecological information:**

**General notes:** Do not allow product to reach ground water, water course or sewage system.

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**

**Recommendation**

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish.

Possible waste code 17 09 04.

**European waste catalogue**

Possible waste code. The concrete waste code depends on the source of the waste.

17 01 01	concrete
16 03 03*	inorganic wastes containing hazardous substances
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 8)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.10.2021

Version number 1

Revision: 28.10.2021

**Trade name weber JB 600/3 P Non-shrink grout frost C50/60-4**

(Contd. of page 7)

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

<b>14.1 UN number or ID number</b> ADR, ADN, IMDG, IATA	Void
<b>14.2 UN proper shipping name</b> ADR, ADN, IMDG, IATA	Void
<b>14.3 Transport hazard class(es)</b> ADR, ADN, IMDG, IATA Class	Void
<b>14.4 Packing group</b> ADR, IMDG, IATA	Void
<b>14.5 Environmental hazards:</b>	Not applicable.
<b>14.6 Special precautions for user</b>	Not applicable.
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
<b>Transport/Additional information:</b>	Not dangerous according to the above specifications.
<b>UN "Model Regulation":</b>	Void

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10) Regulation (EC) No 1272/2008 (CLP)  
Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**REGULATION (EC) No 1907/2006 ANNEX XVII**

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds)  
Conditions of restriction: 47

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**REGULATION (EU) 2019/1148**

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

(Contd. on page 9)



# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2021

Version number 1

Revision: 28.10.2021

**Trade name weber JB 600/3 P Non-shrink grout frost C50/60-4**

(Contd. of page 8)

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

CAS: 7631-99-4 | sodium nitrate

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H272 May intensify fire; oxidiser.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
EUH203 Contains chromium (VI). May produce an allergic reaction.

**Department issuing SDS:**

Saint-Gobain Finland Oy / Weber  
QEHS  
P.O.Box 70 (Strömberginkuja 2)  
FI-00381 Helsinki

**Contact:**

Tel. +358-(0)10-44 22 00  
Fax +358-(0)10-44 22 520

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organisation  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
SVHC: Substances of Very High Concern (REACH regulation)  
vPvB: very Persistent and very Bioaccumulative  
Ox. Sol. 2: Oxidizing solids – Category 2  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3