

Printing date 02.08.2019 Version number 3 Revision: 30.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name webervetonit 3300 Smooth Levelling

Safety data sheet no.: 358P0505

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Construction chemicals Filler and surfacer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2) FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 295 email: info@e-weber.fi www.e-weber.fi

1.4 Emergency telephone number: Tel. +358-(0)10-44 22 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



CHSOS

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

P102 Keep out of reach of children.

P261 Avoid breathing dust.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)



Printing date 02.08.2019 Version number 3 Revision: 30.07.2019

Trade name webervetonit 3300 Smooth Levelling

P313 Get medical advice/attention.

(Contd. of page 1)

2.3 Other hazards

PBT: Does not contain PBT substances. **vPvB**: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Ready-mixed mortar with Portland cement

Dangerous components:			
CAS: 471-34-1 EINECS: 207-439-9 Reg.nr.: 01-2119486795-18-xxxx	calcium carbonate substance with a Community workplace exposure limit	25-50%	
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey	2-5%	

SVHC Void

Additional information

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 0,1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Supply fresh air and to be sure call for a doctor.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Rinse out mouth and then drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

EUG



Printing date 02.08.2019 Version number 3 Revision: 30.07.2019

Trade name webervetonit 3300 Smooth Levelling

(Contd. of page 2)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

The product is not combustible.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Wear protective clothing.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Store in dry conditions.

7.3 Specific end use(s) No further relevant information available.

- EUG

(Contd. on page 4)



Printing date 02.08.2019 Version number 3 Revision: 30.07.2019

Trade name webervetonit 3300 Smooth Levelling

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
	alcium carbonate	
	ed No Effect Level 6.36 mg/m³ (worker local long term value)	
	1.06 mg/m³ (consumer local long term value)	
CAS No Dosi	gnation of material % Type Value Unit	
	7 Siliciumdioxide (Quartzsand)	
	<u> </u>	
TWA (Italy)	Long-term value: 0.025 mg/m³ A2 (r)	
HTP (Finland)	Long-term value: 0.05 mg/m³ respirable fraction	
CAS: 471-34-1 c	alcium carbonate	
LEP (Spain)	Long-term value: 10 mg/m³	
TWA (Italy)	Long-term value: (10) mg/m³ (e)	
VLE (Portugal)	Long-term value: (10) mg/m³ (Irritação)	
CAS: 65997-15-	cement portland, grey	
AGW (Germany)	Long-term value: 5 E mg/m³ DFG	
LEP (Spain)	Long-term value: 4 mg/m³ fracción respirable: e, d	
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4	
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma	
HTP (Finland)	Long-term value: 5* 1** mg/m³ *inhalable, **respirable	

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Use suitable respiratory protective device when high

concentrations are present.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

The hands must be cleaned from the powder before putting on the gloves.

(Contd. on page 5)



Revision: 30.07.2019 Printing date 02.08.2019 Version number 3

Trade name webervetonit 3300 Smooth Levelling

Protective gloves.

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection: Safety glasses.
Body protection: Protective work clothing.

SECTION 9: Physical and chemical	SECTION 9: Physical and chemical properties			
9.1 Information on basic physical and cher	mical properties			
General Information				
Appearance:				
Form:	Powder			
Colour:	Grey			
Odour: Odour threshold:	Specific type Not determined.			
	<11			
pH-value at 20 °C:	×11			
Change in condition				
Initial boiling point and boiling range:	Undetermined.			
Flash point:	Not applicable			
Flammability (solid, gas):	Product is not flammable.			
Ignition temperature:	Not determined.			
Decomposition temperature:	Not determined.			
Explosive properties:	Product does not present an explosion hazard.			
Explosion limits:				
Lower:	Not determined.			
Upper:	Not determined.			
Oxidising properties	Not determined.			
Vapour pressure:	Not applicable.			
Density at 20 °C:	1.4-1.6 g/cm³			
Vapour density	Not applicable.			
Evaporation rate	Not applicable.			
Solubility in / Miscibility with				
Water:	Miscible			
Segregation coefficient (n-octanol/water) l	og			
Pow:	Not determined.			
Viscosity:				
dynamic:	Not determined.			
kinematic:	Not determined.			
Solvent content:	0.00/			
Organic solvents:	0.0 %			
EU-VOC (%)	0.00 %			
EU-VOC (g/L) Solids content:	0.0 g/l 100 %			
Solius Content.	100 %			



Printing date 02.08.2019 Version number 3 Revision: 30.07.2019

Trade name webervetonit 3300 Smooth Levelling

(Contd. of page 5)

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** When mixed with water the product hardens forming a stable non-reactive mass.
- **10.2 Chemical stability** Stable at recommended storage conditions
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

- 10.5 Incompatible materials: Acids, ammonium salts, aluminum, non-precious metals.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compo	nents	Туре	Value	Species				
CAS: 4	CAS: 471-34-1 calcium carbonate							
Oral	LD50	6,450 mg/kg (Rat)						
Dermal	LD50	6,450 mg/kg (Rat)						
CAS: 6	CAS: 65997-16-2 Cement, alumina, chemicals							
Oral	LD50	>2,000 mg/kg (Rat)						
CAS: 6	CAS: 65997-15-1 cement portland, grey							
Dermal	LD50	>2,000 mg/kg (Rabbit)						

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.08.2019 Version number 3 Revision: 30.07.2019

Trade name webervetonit 3300 Smooth Levelling

(Contd. of page 6)

Type of test Effective concentration Method Assessment

CAS: 471-34-1 calcium carbonate

EC50/72h 14 mg/l (Algae)

12.2 Persistence and degradability The product is not biodegradable.

12.3 Bioaccumulative potential Does not accumulate in organisms

Behaviour in environmental systems:

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

Waste disposal key:

The classification in a waste code according to the european waste catalogue (EWC) is to be made in accordance with the regional responsable for waste disposal

European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

17 01 01	concrete	
16 03 03*	inorganic wastes containing hazardous substances	
	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10	
HP4	Irritant - skin irritation and eye damage	

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Thoroughly shake out sacks.

SECTION 14: Transport information

14.1 UN-Number ADR, ADN, IMDG, IATA

Void

(Contd. on page 8)



Printing date 02.08.2019 Version number 3 Revision: 30.07.2019

Trade name webervetonit 3300 Smooth Levelling

	(Contd. of page
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Anne Marpol and the IBC Code	x II of Not applicable.
Transport/Additional information:	Not dangerous according to the abov specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10) Regulation (EC) No 1272/2008 (CLP)

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds)

Conditions of restriction: 47

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Department issuing SDS:

Saint-Gobain Finland Oy / Weber QEHS

(Contd. on page 9)



Printing date 02.08.2019 Version number 3 Revision: 30.07.2019

Trade name webervetonit 3300 Smooth Levelling

(Contd. of page 8)

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 520

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG