

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 4 (replaces version 3)

Revision: 12.12.2022

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier Trade name weber 5400 Heated Floor Screed

Safety data sheet no.: 358P0541 1.2 Relevant identified uses of the substance or mixture and uses advised against Application of the substance / the mixture Construction chemicals Filler and surfacer

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Saint-Gobain Finland Oy / Weber PL 70 (Strömberginkuja 2) FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 295 DL-productsafety.fi@saint-gobain.com www.fi.weber **1.4 Emergency telephone number:** 0800 147 111 (toll-free) 09 471 977 (standard rate) Finnish Poison Information Centre

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Skin Irrit. 2 H315 Causes skin irritation.

Skin IIII. 2 H315 Causes skin IIIIalion.

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. **Hazard pictograms**



Signal word Danger

Hazard-determining components of labelling:cement portland, greyHazard statementsH315 Causes skin irritation.H318 Causes serious eye damage.Precautionary statementsP102Keep out of reach of children.P261Avoid breathing dust.

(Contd. on page 2)

⁻ EUG

according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 12.12.2022

Trade name weber 5400 Heated Floor Screed

(Contd. of page 1)

P280 Wear protective gloves / eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. P310

Dispose of contents/container in accordance with local/regional/national/international P501 regulations.

2.3 Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Ready-mixed mortar with Portland cement

Dangerous components:		
CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	50-75%
CAS: 471-34-1 EINECS: 207-439-9 Reg.nr.: 01-2119486795-18-xxxx	calcium carbonate substance with a Community workplace exposure limit	10-20%
CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, natural substance with a Community workplace exposure limit	5-10%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey	2-5%

SVHC Void

Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelflife, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Supply fresh air and to be sure call for a doctor.

Printing date 12.12.2022

11/0

according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 12.12.2022

Trade name weber 5400 Heated Floor Screed

(Contd. of page 2)

After skin contact

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

Rinse opened eye forat least 15 minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation Risk of eye damage in contact with dry or moist product.

May irritate moist skin in prolonged contact.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray

or alcohol resistant foam.

The product is not combustible.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Wear protective clothing.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 12.12.2022

Printing date 12.12.2022

Trade name weber 5400 Heated Floor Screed

Information about fire - and explosion protection: No special measures required.

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities

Storage

JWe

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Store in dry conditions.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Finland: cement dust

HTP(8h) = 5 mg/m3, inhalable dust

HTP(8h) = 1 mg/m3, respirable dust

DNELs

Γ

DNELS	DNELS				
	CAS: 65997-16-2 Cement, alumina, chemicals				
Inhalative	Derived No Effect Level		2.5 mg/m ³ (worker systemic long term value)		
			5 mg/m³ (worker systemic short term value)		
CAS: 471	-34-1 calcium ca	rbonate			
Inhalative	Derived No Effe	ct Level	6.36 mg/m ³ (worker local long term value)		
			1.06 mg/m³ (consumer local long term value)		
CAS: 777	8-18-9 calcium s	ulphate	, natural		
Oral	Derived No Effe	ct Level	1.52 mg/kgxday (consumer systemic long term value)		
			11.4 mg/kgxday (consumer systemic short term value)		
Inhalative	Derived No Effe	ct Level	21.17 mg/m³ (worker systemic long term value)		
			5,082 mg/m³ (worker systemic short term value)		
			5.29 mg/m ³ (consumer systemic long term value)		
			3,811 mg/m ³ (consumer systemic short term value)		
CAS	lo. / Designatior	n of mat	erial / % / Type / Value / Unit		
CAS: 148	08-60-7 Silicon d	dioxide ((Quartz sand)		
BOELV (E	uropean Union)		rm value: 0.1* mg/m³		
	*respirable fraction				
MAK (Ger			rm value: 0.05 mg/m³		
			ngängige Fraktion		
GV (Denm			rm value: 0.6* 0.2** mg/m³ rm value: 0.3* 0.1** mg/m³		
			total, respirabel, EK		
LEP (Spai			rm value: 0.05 mg/m ³		
			on resp:n,d,y		
TWA (Italy) Long-term value: 0.025 mg			rm value: 0.025 mg/m³		
		A2, (j)			
			(Contd. on page 5)		

(Contd. on page 5)

– EUG –

Safety Data Sheet according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 12.12.2022

Trade name weber 5400 Heated Floor Screed

		(Contd. of page 4)
VLE (Portugal)	Long-term value: 0.025 mg/m³ Resp.;A2; fibrose pulmonar; cancro do pulmão	
OEL (Sweden)	Long-term value: 0.1 mg/m³ C, M, respirabel fraktion	
HTP (Finland)	Long-term value: 0.05 0.1* mg/m³ alveolijae;*sitovat raja-arvot, pöly	
CAS: 471-34-1 calcium c	arbonate	
LEP (Spain)	Long-term value: 10 mg/m³	
TWA (Italy)	Long-term value: (10) mg/m³ (e)	
VLE (Portugal)	Long-term value: (10) mg/m³ (Irritação)	
CAS: 7778-18-9 calcium	sulphate, natural	
AGW (Germany)	Long-term value: 6 A mg/m ³ DFG	
LEP (Spain)	Long-term value: 10 mg/m³ e	
TWA (Italy)	Long-term value: 10 mg/m³ (i)	
VLE (Portugal)	Long-term value: 10 mg/m³ Fração inalável; Sintomas nasais	
CAS: 65997-15-1 cement		
AGW (Germany)	Long-term value: 5 E mg/m³ DFG	
LEP (Spain)	Long-term value: 4 mg/m³ fracción respirable: e, d	
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4	
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma	
HTP (Finland)	Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae	
General protective and H Keep away from foodstuff Immediately remove all so Wash hands before break Avoid contact with the eye Use a moisturising skin cr Respiratory protection: Use suitable respiratory pr concentrations are presen In case of brief exposure of In case of intensive or long Hand protection	s, beverages and feed. biled and contaminated clothing. is and at the end of work. is and skin. eam after processing the product. rotective device when high	
		(Contd. on page 6)



Safety Data Sheet according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 12.12.2022

(Contd. of page 5)

EUG

Trade name weber 5400 Heated Floor Screed

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture. Eye/face protection Safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties			
General Information			
Colour:	Grey		
Odour:	Specific type		
Odour threshold:	Not determined.		
Boiling point or initial boiling point and boiling			
range	Undetermined.		
Flammability	Product is not flammable.		
Lower and upper explosion limit			
Lower:	Not determined.		
Upper:	Not determined.		
Flash point:	Not applicable		
Ignition temperature:	Not determined.		
Decomposition temperature:	Not determined.		
pH at 20 °C	<11		
Viscosity:			
Kinematic viscosity	Not determined.		
dynamic:	Not determined.		
Solubility			
Water:	Miscible		
Partition coefficient n-octanol/water (log value)	Not determined.		
Vapour pressure:	Not applicable.		
Density and/or relative density			
Density at 20 °C:	1.4-1.6 g/cm³		
Vapour density	Not applicable.		
Particle characteristics	See item 3.		
9.2 Other information	No further relevant information available.		
Appearance:			
Form:	Powder		
Important information on protection of health			
and environment, and on safety.			
Explosive properties:	Product does not present an explosion hazard.		
Minimum ignition energy			
Solvent content:			
Organic solvents:	0.0 %		
EU-VOC (%)	0.00 %		
EU-VOC (g/L)			
Solids content:	100 %		
Change in condition			
Softening point/range			
Oxidising properties	Not determined.		
	(Contd. on page 7)		





according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 4 (replaces version 3)

Revision: 12.12.2022

Trade name weber 5400 Heated Floor Screed

		(Contd. of page
Evaporation rate	Not applicable.	
Information with regard to physical has	zard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity

Not reactive under normal conditions of use

In reaction with water the product will harden into a stable mass that is not reactive under normal conditions.

10.2 Chemical stability Stable at recommended storage conditions

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden). Humidity (during storage).

10.5 Incompatible materials:

Acids, ammonium salts, aluminum, non-precious metals.

Acids, ammonium salts, aluminium powder.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met. LD/LC50 values relevant for classification:

Compor	nents	1	Туре	1	Value	1	/ Species
CAS: 65	5997-16	6-2 Cement	, alumina,	cher	nicals		
Oral	LD50	>2,000 mg/	′kg (Rat)				
Dermal	LD50	>2,000 mg/	′kg (Rat)				
							(Contd. on page 8

- FUG

according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 12.12.2022

Trade name weber 5400 Heated Floor Screed

	(Contd. of page 7
CAS: 471-34-1 calcium carbonate	
Oral LD50 6,450 mg/kg (Rat)	
Dermal LD50 6,450 mg/kg (Rat)	
CAS: 7778-18-9 calcium sulphate, natural	
Oral LD50 >2,000 mg/kg (Rat)	
CAS: 65997-15-1 cement portland, grey	
Dermal LD50 >2,000 mg/kg (Rabbit)	
Skin corrosion/irritation	
Causes skin irritation.	
Serious eye damage/irritation	
Causes serious eye damage.	
Respiratory or skin sensitisation Based on available data, the classification criteria	
Germ cell mutagenicity Based on available data, the classification criteria are not n	iet.
Carcinogenicity Based on available data, the classification criteria are not met.	
Reproductive toxicity Based on available data, the classification criteria are not me	
STOT-single exposure Based on available data, the classification criteria are not m	
STOT-repeated exposure Based on available data, the classification criteria are not	met.
Aspiration hazard Based on available data, the classification criteria are not met.	
11.2 Information on other hazards	
Endocrine disrupting properties	
None of the ingredients is listed.	
SECTION 12: Ecological information	
12.1 Toxicity	
Aquatic toxicity: Not classified as harmful to aquatic life	
Type of test / Effective concentration / Method / Assessment	
CAS: 65997-16-2 Cement, alumina, chemicals	
LC50/96h 100 mg/l (Fish)	

EC50/48h 5.4 mg/l (Daphnia magna)

EC50/72h 3.6 mg/l (Algae)

CAS: 471-34-1 calcium carbonate

EC50/72h 14 mg/l (Algae)

CAS: 7778-18-9 calcium sulphate, natural

LC50/48h 79-1,970 mg/l (Daphnia magna)

LC50/96h >79 mg/l (Oryzias latipes (Japanese medaka))

79-2,980 mg/l (Fish)

EC50/72h >79 mg/l (Selenastrum capricornutum (Green algae))

12.2 Persistence and degradability The product is not biodegradable.

12.3 Bioaccumulative potential Does not accumulate in organisms

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 12.12.2022

Trade name weber 5400 Heated Floor Screed

(Contd. of page 8)

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment

CAS: 65997-16-2 Cement, alumina, chemicals

EC 50 (3h) 1,000 mg/l (Activated sludge)

CAS: 7778-18-9 calcium sulphate, natural

EC 50 (3h) >1,000 mg/l (Activated sludge)

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

Waste disposal key:

The classification in a waste code according to the european waste catalogue (EWC) is to be made in accordance with the regional responsable for waste disposal

European waste catalogue				
17 01 01	concrete			
16 03 03*	inorganic wastes containing hazardous substances			
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10			

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations. **Recommended cleaning agent:** Thoroughly shake out sacks.

SECTION 14: Transport information

14.1 UN number or ID number ADR, ADN, IMDG, IATA

Void

14.2 UN proper shipping name ADR, ADN, IMDG, IATA

Void

(Contd. on page 10)

- EUG



according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 12.12.2022

Trade name weber 5400 Heated Floor Screed

	(Contd. of page 9
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordi	ing to
IMO instruments	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII) Regulation (EC) No 1272/2008 (CLP) Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets) Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds)

Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed. **REGULATION (EU) 2019/1148**

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 11)



EUG

according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 12.12.2022

Trade name weber 5400 Heated Floor Screed

(Contd. of page 10) 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation	Expert judgement
, , ,	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS:

Saint-Gobain Finland Oy / Weber QEHS P.O.Box 70 (Strömberginkuja 2) FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 520

Version number of previous version: 3

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern (REACH regulation) vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 * Data compared to the previous version altered. According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

