

Revision: 13.12.2022



## Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 4 (replaces version 3)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name weber 6000 Rapid Screed

Safety data sheet no.: 358P0508

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Construction chemicals Filler and surfacer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

1.4 Emergency telephone number:

0800 147 111 (toll-free) 09 471 977 (standard rate) Finnish Poison Information Centre

### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

5 D 4 11040 O

Eye Dam. 1 H318 Causes serious eye damage.

### 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms** 



GHS05

### Signal word Danger

### Hazard-determining components of labelling:

cement portland, grey

### **Hazard statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

### **Precautionary statements**

P102 Keep out of reach of children.

P261 Avoid breathing dust.

(Contd. on page 2)





Printing date 13.12.2022 Version number 4 (replaces version 3) Revision: 13.12.2022

### Trade name weber 6000 Rapid Screed

(Contd. of page 1)

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### 2.3 Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

### Results of PBT and vPvB assessment

**PBT:** Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

**Description:** Ready-mixed mortar with Portland cement

Dangerous components:		
CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	75-100%
CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, natural substance with a Community workplace exposure limit	2-5%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey	2-5%

### **SVHC** Void

#### **Additional information**

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

After inhalation Supply fresh air and to be sure call for a doctor.

### After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

(Contd. on page 3)





Printing date 13.12.2022

Version number 4 (replaces version 3)

### Trade name weber 6000 Rapid Screed

(Contd. of page 2)

Revision: 13.12.2022

### After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

Rinse opened eye for at least 15 minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

### After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

### 4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation Risk of eye damage in contact with dry or moist product.

May irritate moist skin in prolonged contact.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

### Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray

or alcohol resistant foam.

The product is not combustible.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

### 5.3 Advice for firefighters

Protective equipment: No special measures required.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Wear protective clothing.

**6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.

### 6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)



Printing date 13.12.2022 Version number 4 (replaces version 3) Revision: 13.12.2022

#### Trade name weber 6000 Rapid Screed

(Contd. of page 3)

## 7.2 Conditions for safe storage, including any incompatibilities Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required. Further information about storage conditions: Store in dry conditions.

7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Finland: cement dust

HTP(8h) = 5 mg/m3, inhalable dust HTP(8h) = 1 mg/m3, respirable dust

DNELs				
CAS: 659	CAS: 65997-16-2 Cement, alumina, chemicals			
Inhalative	Derived No Effect Level	2.5 mg/m³ (worker systemic long term value)		
		5 mg/m³ (worker systemic short term value)		
CAS: 777	CAS: 7778-18-9 calcium sulphate, natural			
Oral	Derived No Effect Level	1.52 mg/kgxday (consumer systemic long term value)		
		11.4 mg/kgxday (consumer systemic short term value)		
Inhalative	Derived No Effect Level	21.17 mg/m³ (worker systemic long term value)		
		5,082 mg/m³ (worker systemic short term value)		
		5.29 mg/m³ (consumer systemic long term value)		
		3,811 mg/m³ (consumer systemic short term value)		

### CAS No. / Designation of material / % / Type / Value / Unit CAS: 14808-60-7 Silicon dioxide (Quartz sand) BOELV (European Union) Long-term value: 0.1\* mg/m<sup>3</sup> \*respirable fraction MAK (Germany) Long-term value: 0.05 mg/m<sup>3</sup> alveolengängige Fraktion Short-term value: 0.6\* 0.2\*\* mg/m3 GV (Denmark) Long-term value: 0.3\* 0.1\*\* mg/m<sup>3</sup> \*total:,\*\*total, respirabel, EK Long-term value: 0.05 mg/m<sup>3</sup> LEP (Spain) \*Fracción resp:n,d,y Long-term value: 0.025 mg/m<sup>3</sup> TWA (Italy) A2, (j) VLE (Portugal) Long-term value: 0.025 mg/m<sup>3</sup> Resp.;A2; fibrose pulmonar; cancro do pulmão Long-term value: 0.1 mg/m<sup>3</sup> OEL (Sweden) C, M, respirabel fraktion HTP (Finland) Long-term value: 0.05 0.1\* mg/m<sup>3</sup> alveolijae;\*sitovat raja-arvot, pöly

(Contd. on page 5)



Printing date 13.12.2022 Version number 4 (replaces version 3) Revision: 13.12.2022

#### Trade name weber 6000 Rapid Screed

	(Contd. of	f page			
CAS: 7778-18-9 calcium sulphate, natural					
AGW (Germany)	Long-term value: 6 A mg/m³ DFG				
LEP (Spain)	Long-term value: 10 mg/m³ e				
TWA (Italy)	Long-term value: 10 mg/m³ (i)				
VLE (Portugal)	Long-term value: 10 mg/m³ Fração inalável; Sintomas nasais				
CAS: 65997-15-1 cement portland, grey					
AGW (Germany)	Long-term value: 5 E mg/m³ DFG				
LEP (Spain)	Long-term value: 4 mg/m³ fracción respirable: e, d				
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4				
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma				
HTP (Finland)	Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae				

#### 8.2 Exposure controls

## Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

### Respiratory protection:

Use suitable respiratory protective device when high

concentrations are present.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Filter P3.

### Hand protection

The hands must be cleaned from the powder before putting on the gloves.

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

**Eye/face protection** Tightly sealed goggles

**Body protection:** Protective work clothing.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

**General Information** 

Colour: Grey

Odour: Specific type

(Contd. on page 6)



Printing date 13.12.2022 Version number 4 (replaces version 3) Revision: 13.12.2022

Trade name weber 6000 Rapid Screed

(Contd. of page 5)

Odour threshold: Not determined.

Boiling point or initial boiling point and boiling

range Undetermined.

**Flammability** Product is not flammable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicableIgnition temperature:Not determined.Decomposition temperature:Not determined.

pH at 20 °C <11

**Viscosity:** 

**Kinematic viscosity dynamic:**Not determined.

Not determined.

Solubility

Water: Miscible

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure:

Not applicable.

Density and/or relative density

Density at 20 °C:1.4-1.6 g/cm³Vapour densityNot applicable.Particle characteristicsSee item 3.

**9.2 Other information**No further relevant information available.

Appearance:

Form: Powder

Important information on protection of health

and environment, and on safety.

**Explosive properties:** Product does not present an explosion hazard.

Minimum ignition energy

Solvent content:

Organic solvents: 0.0 % EU-VOC (%) 0.00 %

EU-VOC (g/L)

Solids content: 100 %

Change in condition

Softening point/range

Oxidising properties Not determined. Evaporation rate Not applicable.

Information with regard to physical hazard

classes

**Explosives** Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void

(Contd. on page 7)



Printing date 13.12.2022 Version number 4 (replaces version 3) Revision: 13.12.2022

Trade name weber 6000 Rapid Screed

(Contd. of page 6) **Pyrophoric solids** Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void **Desensitised explosives** Void

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

When mixed with water the product hardens forming a stable non-reactive mass.

In reaction with water the product will harden into a stable mass that is not reactive under normal conditions.

- 10.2 Chemical stability Stable at recommended storage conditions
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden). Humidity (during storage).

### 10.5 Incompatible materials:

Acids, ammonium salts, aluminum, non-precious metals.

Acids, ammonium salts, aluminium powder.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compo	nents	I	Type	1	Value	1	/ Species	
CAS: 68	5997-1	6-2 Cement	t, alumina,	cher	nicals			
Oral	LD50	>2,000 mg/	/kg (Rat)					
Dermal	LD50	>2,000 mg/	/kg (Rat)					
CAS: 77	CAS: 7778-18-9 calcium sulphate, natural							
Oral	LD50	>2,000 mg/	/kg (Rat)					
CAS: 68	CAS: 65997-15-1 cement portland, grey							
Dermal	LD50	>2,000 mg/	/kg (Rabbit	)				

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 13.12.2022

Version number 4 (replaces version 3)

### Trade name weber 6000 Rapid Screed

(Contd. of page 7)

Revision: 13.12.2022

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

### **Endocrine disrupting properties**

None of the ingredients is listed.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of te	Type of test / Effective concentration / Method / Assessment				
CAS: 6599	CAS: 65997-16-2 Cement, alumina, chemicals				
LC50/96h	100 mg/l (Fish)				
EC50/48h	5.4 mg/l (Daphnia magna)				
EC50/72h	3.6 mg/l (Algae)				
CAS: 7778	CAS: 7778-18-9 calcium sulphate, natural				
LC50/48h	79-1,970 mg/l (Daphnia magna)				
LC50/96h	>79 mg/l (Oryzias latipes (Japanese medaka))				
	79-2,980 mg/l (Fish)				
EC50/72h	>79 mg/l (Selenastrum capricornutum (Green algae))				

- 12.2 Persistence and degradability The product is not biodegradable.
- 12.3 Bioaccumulative potential Does not accumulate in organisms
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects** No further relevant information available.

### Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

### Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment		
CAS: 65997-16-2 Cement, alumina, chemicals		
EC 50 (3h) 1,000 mg/l (Activated sludge)		
CAS: 7778-18-9 calcium sulphate, natural		
EC 50 (3h) >1,000 mg/l (Activated sludge)		

### Additional ecological information:

### **General notes:**

Do not allow product to reach ground water, water course or sewage system, even in small quantities.





Printing date 13.12.2022 Version number 4 (replaces version 3) Revision: 13.12.2022

Trade name weber 6000 Rapid Screed

(Contd. of page 8)

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

#### Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

### Waste disposal key:

The classification in a waste code according to the european waste catalogue (EWC) is to be made in accordance with the regional responsable for waste disposal

European waste catalogue			
17 01 01	concrete		
16 03 03*	inorganic wastes containing hazardous substances		
	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10		

### **Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleaning agent: Thoroughly shake out sacks.

SECTION 14: Transport informat	tion
14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according IMO instruments	ng to Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications
UN "Model Regulation":	Void

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

(Contd. on page 10)





Printing date 13.12.2022

Version number 4 (replaces version 3)

### Trade name weber 6000 Rapid Screed

(Contd. of page 9)

Revision: 13.12.2022

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)
Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10)

### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

### **REGULATION (EC) No 1907/2006 ANNEX XVII**

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds)

Conditions of restriction: 47

## DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

### **REGULATION (EU) 2019/1148**

## Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

### Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

## Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008		
Skin corrosion/irritation	Expert judgement	
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

### **Department issuing SDS:**

Saint-Gobain Finland Oy / Weber QEHS

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

(Contd. on page 11)





Printing date 13.12.2022 Version number 4 (replaces version 3) Revision: 13.12.2022

### Trade name weber 6000 Rapid Screed

(Contd. of page 10)

#### Contact:

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 520

### Version number of previous version: 3

### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

### \* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

FUG