Revision: 19.06.2023



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2023

Version number 4 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weber rex fix

Safety data sheet no.: 358P0480

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Construction chemicals

Tile adhesive

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

1.4 Emergency telephone number:

0800 147 111 (toll-free)

09 471 977 (standard rate)

Finnish Poison Information Centre

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

Burnt Oil Shale (BOS)

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

(Contd. on page 2)





Printing date 19.06.2023 Version number 4 (replaces version 3) Revision: 19.06.2023

Trade name weber rex fix

(Contd. of page 1)

Precautionary statements

P102 Keep out of reach of children.

P261 Avoid breathing dust.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Ready-mixed mortar with Portland cement

CAS: 14808-60-7	Silicon dioxide (Quartz sand)	
EINECS: 238-878-4	substance with a Community workplace exposure limit	
CAS: 65997-15-1	cement portland, grey	25-50%
EINECS: 266-043-4	Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203	
	Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	
CAS: 471-34-1	calcium carbonate	10-20%
EINECS: 207-439-9	substance with a Community workplace exposure limit	
Reg.nr.: 01-2119486795-18-xxx		
CAS: 93685-99-5	Burnt Oil Shale (BOS)	<5%
EINECS: 297-648-1	♦ STOT RE 2, H373; ♦ Eye Dam. 1, H318; ♦ STOT SE	
Reg.nr.: 01-2119703178-42-xxx	x 3, H335	

SVHC Void

Additional information

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

- EUG





Printing date 19.06.2023 Version number 4 (replaces version 3) Revision: 19.06.2023

Trade name weber rex fix

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Supply fresh air and to be sure call for a doctor.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

The product is not combustible.

Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Avoid formation of dust.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)



Printing date 19.06.2023 Version number 4 (replaces version 3) Revision: 19.06.2023

Trade name weber rex fix

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs				
CAS: 471-	-34-1 calcium ca	arbonate		
		ct Level 6.36 mg/m³ (worker local long term value)		
		1.06 mg/m³ (consumer local long term value)		
CAS: 93685-99-5 Burnt Oil Shale (BOS)				
Inhalative	Derived No Effe	ct Level 0.233 mg/m³ (worker local long term value)		
		0.233 mg/m³ (consumer local short term value)		
CAS N	lo. / Designatio	n of material / % / Type / Value / Unit		
CAS: 1480	08-60-7 Silicon	dioxide (Quartz sand)		
BOELV (E	uropean Union)	Long-term value: 0.1* mg/m³		
		*respirable fraction		
MAK (Geri	many)	Long-term value: 0.05 mg/m³		
		alveolengängige Fraktion		
GV (Denm	nark)	Short-term value: 0.6* 0.2** mg/m³		
		ong-term value: 0.3* 0.1** mg/m³ total:,**total, respirabel: K		
LEP (Spai	n)	Long-term value: 0.05 mg/m³		
LLI (Opui	,	*Fracción resp:n,d,y		
TWA (Italy	()	term value: 0.025 mg/m³		
	•	A2, (j)		
VLE (Portu	ugal)	Long-term value: 0.05 mg/m³		
		Resp.;A2; fibrose pulmonar; cancro do pulmão		
		Long-term value: 0.1 mg/m³		
		C, M, respirabel fraktion		
		Long-term value: 0.05 0.1* mg/m³ alveolijae;*sitovat raja-arvot, pöly		
CAS: 65997-15-1 cement portland, grey				
•		Long-term value: 5 E mg/m³		
	,	DFG		
LEP (Spain) Long-ter		Long-term value: 4 mg/m³		
		fracción respirable: e, d		

(Contd. on page 5)



Printing date 19.06.2023 Version number 4 (replaces version 3) Revision: 19.06.2023

Trade name weber rex fix

		(Contd. of page 4)		
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4			
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma			
HTP (Finland)	Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae			
CAS: 471-34-1 calcium carbonate				
LEP (Spain)	Long-term value: 10 mg/m³			
TWA (Italy)	Long-term value: (10) mg/m³ (e)			
VLE (Portugal)	Long-term value: (10) mg/m³ (Irritação)			

8.2 Exposure controls

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Protective gloves.

The hands must be cleaned from the powder before putting on the gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Eye/face protection Safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour: Grey

Odour: Specific type
Odour threshold: Not determined.
Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range Undetermined.

Flammability Product is not flammable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicableAuto-ignition temperature:Not determined.

(Contd. on page 6)





Printing date 19.06.2023 Version number 4 (replaces version 3) Revision: 19.06.2023

Trade name weber rex fix

(Contd. of page 5)

Decomposition temperature: Not determined.

pH at 20 °C 12-13 (DIN 19261)

In water

Viscosity:

Kinematic viscosity dynamic:Not determined.
Not determined.

Solubility

Water: Slightly soluble Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure: Not applicable.

Density and/or relative density

Density at 20 °C: 1.4-1.65 g/cm³ Vapour density Not applicable.

Particle characteristics

See section 3.

9.2 Other informationNo further relevant information available.

Appearance:

Form: Powder

Important information on protection of health

and environment, and on safety.

Explosive properties: Product does not present an explosion hazard.

Minimum ignition energy

Solvent content:

Organic solvents: 0.0 %

EU-VOC (q/L)

Solids content: 100.0 %

Change in condition Softening point/range

Oxidising propertiesNot determined.Evaporation rateNot applicable.

Information with regard to physical hazard

classes

Explosives Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit

flammable gases in contact with water

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Void

(Contd. on page 7)





Printing date 19.06.2023 Version number 4 (replaces version 3) Revision: 19.06.2023

Trade name weber rex fix

(Contd. of page 6)

Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity When mixed with water the product hardens forming a stable non-reactive mass.
- 10.2 Chemical stability Stable at recommended storage conditions
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

- 10.5 Incompatible materials: Acids, ammonium salts, aluminum, non-precious metals.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compo	nents	1	Type	1	Value	1	Species	
CAS: 65	CAS: 65997-15-1 cement portland, grey							
Dermal	Dermal LD50 >2,000 mg/kg (Rabbit)							
CAS: 47	CAS: 471-34-1 calcium carbonate							
Oral	LD50	6,450 mg/kg	g (Rat)					
Dermal	LD50	6,450 mg/kg	g (Rat)					
CAS: 93685-99-5 Burnt Oil Shale (BOS)								
Oral	LD50	>2,000 mg/	kg (Rat)					

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Not classified as harmful to aquatic life



Printing date 19.06.2023 Version number 4 (replaces version 3) Revision: 19.06.2023

Trade name weber rex fix

(Contd. of page 7)

Type of test	Type of test / Effective concentration / Method / Assessment		
CAS: 471-34	CAS: 471-34-1 calcium carbonate		
EC50/72h	14 mg/l (Algae)		
CAS: 93685-	CAS: 93685-99-5 Burnt Oil Shale (BOS)		
EC50/48h	100 mg/l (Daphnia magna)		
EC50/72h	82.7 mg/l (Algae)		
NOEC (72h)	3.2 mg/l (Algae)		
NOEC (21d)	1 mg/l (Daphnia magna)		

12.2 Persistence and degradability The product is not biodegradable.

12.3 Bioaccumulative potential Does not accumulate in organisms

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment
CAS: 93685-99-5 Burnt Oil Shale (BOS)
EC 50 (3h) 1,000 mg/l (Activated sludge)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

European waste catalogue		
17 01 01	concrete	
16 03 03*	inorganic wastes containing hazardous substances	
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 9)



Printing date 19.06.2023 Version number 4 (replaces version 3) Revision: 19.06.2023

Trade name weber rex fix

Recommended cleaning agent: Thoroughly shake out sacks.

(Contd. of page 8)

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
	1014	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according to		
IMO instruments	Not applicable.	
Transport/Additional information:	Not dangerous according to the above specifications	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds)

Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 10)





Printing date 19.06.2023 Version number 4 (replaces version 3) Revision: 19.06.2023

Trade name weber rex fix

(Contd. of page 9)

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However,

this shall not constitute a guarantee for any specific product

features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation	The classification of the mixture is generally based on
Serious eye damage/irritation	the calculation method using substance data according
Specific target organ toxicity (single exposure)	to Regulation (EC) No 1272/2008.

Department issuing SDS:

Saint-Gobain Finland Oy / Weber

QEHS

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 520

Version number of previous version: 3

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 11)





Printing date 19.06.2023 Version number 4 (replaces version 3) Revision: 19.06.2023

Trade name weber rex fix

(Contd. of page 10)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

- EUG -