Revision: 05.10.2023



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 05.10.2023

Version number 3 (replaces version 2)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: weber OL 15 P Frost thin layer mortar

Safety data sheet no.: 358P0715

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

1.4 Emergency telephone number:

0800 147 111 (toll-free)

09 471 977 (standard rate)

Finnish Poison Information Centre

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

cement, portland, white cement portland, grey

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Precautionary statements

P102 Keep out of reach of children.

(Contd. on page 2)



Printing date 05.10.2023 Version number 3 (replaces version 2) Revision: 05.10.2023

Trade name: weber OL 15 P Frost thin layer mortar

(Contd. of page 1)

P261 Avoid breathing dust.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

2.3 Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Ready-mixed mortar with Portland cement

| Dangerous components: | | |
|---|---|--------|
| CAS: 1317-65-3 EINECS: 215-279-6 | calcium carbonate substance with a Community workplace exposure limit | 25-50% |
| CAS: 65997-15-1 EINECS: 266-043-4 | cement, portland, white | 25-50% |
| CAS: 14808-60-7 EINECS: 238-878-4 | Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit | 10-20% |
| CAS: 65997-15-1 EINECS: 266-043-4 | cement portland, grey Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 % | 2-5% |
| CAS: 7631-99-4 EINECS: 231-554-3 Reg.nr.: 01-2119488221-41-xxxx | sodium nitrate Ox. Sol. 2, H272; Use Irrit. 2, H319 | 1-2% |
| CAS: 471-34-1 EINECS: 207-439-9 Reg.nr.: 01-2119486795-18-xxxx | calcium carbonate substance with a Community workplace exposure limit | 1-2% |

SVHC Void

(Contd. on page 3)



Printing date 05.10.2023 Version number 3 (replaces version 2) Revision: 05.10.2023

Trade name: weber OL 15 P Frost thin layer mortar

(Contd. of page 2)

Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Supply fresh air and to be sure call for a doctor.

After skin contact Immediately wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

The product is not combustible.

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

FUG



Printing date 05.10.2023 Version number 3 (replaces version 2) Revision: 05.10.2023

Trade name: weber OL 15 P Frost thin layer mortar

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Any unavoidable deposit of dust must be regularly removed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Store in dry conditions.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

| DNELs | |
|---|---|
| CAS: 471-34-1 calcium ca | |
| Inhalative Derived No Effe | ct Level 6.36 mg/m³ (worker local long term value) |
| | 1.06 mg/m³ (consumer local long term value) |
| CAS No. / Designation | n of material / % / Type / Value / Unit |
| CAS: 1317-65-3 calcium | carbonate |
| TWA (Italy) | Long-term value: 10 mg/m³ (e) |
| CAS: 65997-15-1 cement | portland, white |
| AGW (Germany) | Long-term value: 5 E mg/m³ DFG |
| LEP (Spain) | Long-term value: 4 mg/m³ fracción respirable: e, d |
| TWA (Italy) Long-term value: 1 mg/m³ (e, j), A4 | |
| VLE (Portugal) | Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma |
| HTP (Finland) | Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae |
| CAS: 14808-60-7 Silicon | dioxide (Quartz sand) |
| BOELV (European Union) | Long-term value: 0.1* mg/m³ *respirable fraction |
| MAK (Germany) Long-term value: 0.05 mg/m³ alveolengängige Fraktion | |
| GV (Denmark) | Short-term value: 0.6* 0.2** mg/m³ Long-term value: 0.3* 0.1** mg/m³ *total:,**total, respirabel: K |
| | (Contd. on pa |



Printing date 05.10.2023 Version number 3 (replaces version 2) Revision: 05.10.2023

Trade name: weber OL 15 P Frost thin layer mortar

| | | (Contd. of page 4) |
|-------------------------|--|--------------------|
| LEP (Spain) | Long-term value: 0.05 mg/m³ *Fracción resp:n,d,y | |
| TWA (Italy) | Long-term value: 0.025 mg/m³ A2, (j) | |
| VLE (Portugal) | Long-term value: 0.05 mg/m³ Resp.;A2; fibrose pulmonar; cancro do pulmão | |
| OEL (Sweden) | Long-term value: 0.1 mg/m³ C, M, respirabel fraktion | |
| HTP (Finland) | Long-term value: 0.05 0.1* mg/m³ alveolijae;*sitovat raja-arvot, pöly | |
| CAS: 65997-15-1 cement | portland, grey | |
| AGW (Germany) | Long-term value: 5 E mg/m³ DFG | |
| LEP (Spain) | Long-term value: 4 mg/m³ fracción respirable: e, d | |
| TWA (Italy) | Long-term value: 1 mg/m³ (e, j), A4 | |
| VLE (Portugal) | Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma | |
| HTP (Finland) | Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae | |
| CAS: 471-34-1 calcium c | arbonate | |
| LEP (Spain) | Long-term value: 10 mg/m³ | |
| TWA (Italy) | Long-term value: (10) mg/m³ (e) | |
| VLE (Portugal) | Long-term value: (10) mg/m³ (Irritação) | |

8.2 Exposure controls

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Filter P3.

Hand protection

Protective gloves.

The hands must be cleaned from the powder before putting on the gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Check protective gloves prior to each use for their proper condition.

Eye/face protection Tightly sealed goggles

(Contd. on page 6)





Revision: 05.10.2023 Printing date 05.10.2023 Version number 3 (replaces version 2)

Trade name: weber OL 15 P Frost thin layer mortar

Body protection: Protective work clothing.

(Contd. of page 5)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour: Whitish Odour: Specific type **Odour threshold:** Not determined. **Melting point/freezing point:** Undetermined.

Boiling point or initial boiling point and boiling

Undetermined. range

Flammability Product is not flammable.

Lower and upper explosion limit

Lower: Not determined. Upper: Not determined. Not applicable Flash point: **Auto-ignition temperature:** Not determined. **Decomposition temperature:** Not determined. pН

12-13

In water

Viscosity:

Kinematic viscosity Not determined. dynamic: Not determined.

Solubility

Water: Miscible

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure: Not applicable.

Density and/or relative density

Density: 1.2-1.7 g/cm³ Vapour density Not applicable.

Particle characteristics

See section 3.

9.2 Other information No further relevant information available.

Appearance:

Form: Powder

Important information on protection of health

and environment, and on safety.

Explosive properties: Product does not present an explosion hazard.

Minimum ignition energy

Solvent content:

Organic solvents: 0.0 %

EU-VOC (g/L)

Solids content: 100.0 %

Change in condition Softening point/range

Oxidising properties Not determined.

(Contd. on page 7)



Printing date 05.10.2023 Version number 3 (replaces version 2) Revision: 05.10.2023

Trade name: weber OL 15 P Frost thin layer mortar

| | | (Contd. of page |
|---|-----------------|-----------------|
| Evaporation rate | Not applicable. | |
| Information with regard to physical haz | zard | |
| classes | | |
| Explosives | Void | |
| Flammable gases | Void | |
| Aerosols | Void | |
| Oxidising gases | Void | |
| Gases under pressure | Void | |
| Flammable liquids | Void | |
| Flammable solids | Void | |
| Self-reactive substances and mixtures | Void | |
| Pyrophoric liquids | Void | |
| Pyrophoric solids | Void | |
| Self-heating substances and mixtures | Void | |
| Substances and mixtures, which emit | | |
| flammable gases in contact with water | Void | |
| Oxidising liquids | Void | |
| Oxidising solids | Void | |
| Organic peroxides | Void | |
| Corrosive to metals | Void | |
| Desensitised explosives | Void | |

SECTION 10: Stability and reactivity

- 10.1 Reactivity When mixed with water the product hardens forming a stable non-reactive mass.
- 10.2 Chemical stability Stable at recommended storage conditions
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

- 10.5 Incompatible materials: Acids, ammonium salts, aluminum, non-precious metals.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

| Component | s / | Type | 1 | Value | 1 | Species | |
|------------|-------------|---------------|-------|-------|---|---------|--|
| CAS: 1317- | 5-3 calcium | carbonate | | | | | |
| Oral LD5 | 0 >5,000 mg | /kg (Rat) | | | | | |
| CAS: 65997 | -15-1 cemen | , portland, v | white |) | | | |
| Dermal LD5 | 0 >2,000 mg | /kg (Rabbit) | | | | | |
| CAS: 65997 | -15-1 cemen | portland, g | rey | | | | |
| Dermal LD5 | 0 >2,000 mg | /kg (Rabbit) | | | | | |

(Contd. on page 8)



Printing date 05.10.2023 Version number 3 (replaces version 2) Revision: 05.10.2023

Trade name: weber OL 15 P Frost thin layer mortar

| | | | (Contd. of page 7) |
|---------|---------|--------------------|--------------------|
| CAS: 76 | 631-99 | 4 sodium nitrate | |
| Oral | LD50 | 3,430 mg/kg (Rat) | |
| Dermal | LD50 | >5,000 mg/kg (Rat) | |
| CAS: 47 | 71-34-1 | calcium carbonate | |
| Oral | LD50 | 6,450 mg/kg (Rat) | |
| Dermal | LD50 | 6,450 mg/kg (Rat) | |

Skin corrosion/irritation

Causes skin irritation.

| • | | | | | | |
|-------------------------------|--|--|--|--|--|--|
| Serious eye damage/irritation | | | | | | |
| CAS: 7631-99-4 | CAS: 7631-99-4 sodium nitrate | | | | | |
| Irritation of eyes | Irritation of eyes OECD 405 Acute Eye Irritation/Corrosion 2.5 points /(72h) (rabbit corneal haze) | | | | | |
| | | 2.5 points /(72h) (rabbit edema of conjunctiva) | | | | |
| | | 1 points /(72h) (rabbit iris lesion) | | | | |
| | | 2.5 points /(72h) (rabbit redenning of conjuntive) | | | | |

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

| Type of te | Type of test / Effective concentration / Method / Assessment | | | | |
|------------|--|--|--|--|--|
| CAS: 1317 | CAS: 1317-65-3 calcium carbonate | | | | |
| LC50/96h | >10,000 mg/l (Oncorhynchus mykiss (Rainbow trout)) | | | | |
| EC50/48h | >1,000 mg/l (Daphnia magna) | | | | |
| EC50/72h | >200 mg/l (Algae) | | | | |
| CAS: 7631 | -99-4 sodium nitrate | | | | |
| LC50/48h | 10 mg/l (Fish) | | | | |
| LC50/96h | 100-12,000 mg/l (Fish) | | | | |
| EC50/24h | 8,609 mg/l (Daphnia magna) | | | | |
| CAS: 471- | CAS: 471-34-1 calcium carbonate | | | | |
| EC50/72h | 14 mg/l (Algae) | | | | |

12.2 Persistence and degradability The product is not biodegradable.

(Contd. on page 9)



Printing date 05.10.2023 Version number 3 (replaces version 2) Revision: 05.10.2023

Trade name: weber OL 15 P Frost thin layer mortar

(Contd. of page 8)

12.3 Bioaccumulative potential Does not accumulate in organisms

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.vPvB: Does not contain vPvB substances.12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Behaviour in sewage processing plants:

| Type of test / Effective concentration / Method / Assessment | | |
|--|--|--|
| CAS: 7631-99-4 sodium nitrate | | |
| EC 50 (3h) 1,000 mg/l (Activated sludge) | | |

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

| European | European waste catalogue | | | | |
|-----------|--|--|--|--|--|
| 17 01 01 | concrete | | | | |
| 16 03 03* | inorganic wastes containing hazardous substances | | | | |
| 10 13 11 | wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10 | | | | |
| HP4 | Irritant - skin irritation and eye damage | | | | |
| HP5 | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity | | | | |

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

| 14.1 UN number or ID number | | |
|---------------------------------|------|--|
| ADR, ADN, IMDG, IATA | Void | |
| 14.2 UN proper shipping name | | |
| ADR, ADN, IMDG, IATA | Void | |
| 14.3 Transport hazard class(es) | | |
| ADR, ADN, IMDG, IATA | | |
| Class | Void | |

(Contd. on page 10)



Printing date 05.10.2023 Version number 3 (replaces version 2) Revision: 05.10.2023

Trade name: weber OL 15 P Frost thin layer mortar

| | | (Contd. of page 9) |
|---|---------------------------------|--------------------|
| 14.4 Packing group ADR, IMDG, IATA | Void | |
| 14.5 Environmental hazards: | Not applicable. | |
| 14.6 Special precautions for user | Not applicable. | |
| 14.7 Maritime transport in bulk accordi IMO instruments | ng to Not applicable. | |
| UN "Model Regulation": | Void | |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10)

Portland cement clinker is exempt from REACH registration (Article 2.7b and Annex V, section 10).

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

CAS: 7631-99-4 sodium nitrate

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

– EUG





Printing date 05.10.2023 Version number 3 (replaces version 2) Revision: 05.10.2023

Trade name: weber OL 15 P Frost thin layer mortar

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H272 May intensify fire; oxidiser.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS:

Saint-Gobain Finland Oy / Weber

QEHS

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 520

Version number of previous version: 2

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent. Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Ox. Sol. 2: Oxidizing solids - Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 12)





Printing date 05.10.2023 Version number 3 (replaces version 2) Revision: 05.10.2023

Trade name: weber OL 15 P Frost thin layer mortar

(Contd. of page 11)

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG -