

**Safety Data Sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name: **weberfloor 4660N Marine Elastic**

Safety data sheet no.: 358P0570

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Application of the substance / the mixture**

Construction chemicals  
Filler and surfacer

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:**

Saint-Gobain Finland Oy / Weber  
PL 70  
(Strömberginkuja 2)  
FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00  
Fax +358-(0)10-44 22 295  
DL-productsafety.fi@saint-gobain.com  
www.fi.weber

**1.4 Emergency telephone number:**

0800 147 111 (toll-free)  
09 471 977 (standard rate)  
Finnish Poison Information Centre

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

**2.2 Label elements**

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**



GHS05

**Signal word** Danger

**Hazard-determining components of labelling:**

cement portland, grey

**Hazard statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

**Precautionary statements**

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

(Contd. on page 2)

EUG

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362 Take off contaminated clothing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

### Results of PBT and vPvB assessment

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Description:** Ready-mixed mortar with Portland cement

#### Dangerous components:

CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	50-75%
CAS: 471-34-1 EINECS: 207-439-9 Reg.nr.: 01-2119486795-18-xxxx	Calcium Carbonate substance with a Community workplace exposure limit	5-10%
CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, different hydrate levels CaSO <sub>4</sub> x n H <sub>2</sub> O (n = 0; 1/2; 2) substance with a Community workplace exposure limit	5-10%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	2-5%

**SVHC** Void

#### Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

For the wording of the listed hazard statements refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General information** Immediately remove any clothing soiled by the product.

(Contd. on page 3)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 2)

**After inhalation** Supply fresh air and to be sure call for a doctor.**After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact**

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

**After swallowing**

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

**4.2 Most important symptoms and effects, both acute and delayed**

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media****Suitable extinguishing agents**CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

The product is not combustible.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**5.3 Advice for firefighters****Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Avoid formation of dust.

Wear protective clothing.

**6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.**6.3 Methods and material for containment and cleaning up:**

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

**7.1 Precautions for safe handling**

Prevent formation of dust.

Provide suction extractors if dust is formed.

Avoid contact with skin and eyes.

**Information about fire - and explosion protection:** No special measures required.

(Contd. on page 4)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 3)

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

#### Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Store in dry conditions.

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

DNELs		
<b>CAS: 65997-16-2 Cement, alumina, chemicals</b>		
Inhalative	Derived No Effect Level	2.5 mg/m <sup>3</sup> (worker systemic long term value) 5 mg/m <sup>3</sup> (worker systemic short term value)
<b>CAS: 471-34-1 Calcium Carbonate</b>		
Oral	Derived No Effect Level	6.1 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	6.36 mg/m <sup>3</sup> (worker local long term value) 1.06 mg/m <sup>3</sup> (consumer local long term value)
<b>CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO<sub>4</sub> x n H<sub>2</sub>O (n = 0; 1/2; 2)</b>		
Oral	Derived No Effect Level	1.52 mg/kgxday (consumer systemic long term value) 11.4 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	21.17 mg/m <sup>3</sup> (worker systemic long term value) 5,082 mg/m <sup>3</sup> (worker systemic short term value) 5.29 mg/m <sup>3</sup> (consumer systemic long term value) 3,811 mg/m <sup>3</sup> (consumer systemic short term value)
PNECs		
<b>CAS: 65997-16-2 Cement, alumina, chemicals</b>		
Predicted No-Effect Concentration	260 mg/l (fresh water rating factor)	
CAS No. / Designation of material / % / Type / Value / Unit		
<b>CAS: 14808-60-7 Silicon dioxide (Quartz sand)</b>		
BOELV (European Union)	Long-term value: 0.1* mg/m <sup>3</sup> *respirable fraction	
MAK (Germany)	alveolengängige Fraktion	
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m <sup>3</sup> Long-term value: 0.3* 0.1** mg/m <sup>3</sup> *total; **total, respirabel: EK	
LEP (Spain)	Long-term value: 0.05 mg/m <sup>3</sup> *Fracción resp:n,d,y	
TWA (Italy)	Long-term value: 0.025 mg/m <sup>3</sup> A2, (j)	

(Contd. on page 5)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 4)

VLE (Portugal)	Long-term value: 0.025 mg/m <sup>3</sup> Resp.;A2; fibrose pulmonar; cancro do pulmão
OEL (Sweden)	Long-term value: 0.1 mg/m <sup>3</sup> C, M, respirabel fraktion
HTP (Finland)	Long-term value: 0.05 0.1* mg/m <sup>3</sup> alveolijae;*sitovat raja-arvot, pöly
<b>CAS: 471-34-1 Calcium Carbonate</b>	
LEP (Spain)	Long-term value: 10 mg/m <sup>3</sup>
TWA (Italy)	Long-term value: (10) mg/m <sup>3</sup> (e)
VLE (Portugal)	Long-term value: (10) mg/m <sup>3</sup> (Irritação)
<b>CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO<sub>4</sub> x n H<sub>2</sub>O (n = 0; 1/2; 2)</b>	
MAK (Germany)	Long-term value: 4E** mg/m <sup>3</sup> alveoleng.: Abschn.IIIb.*einatembar:Abschn.Vf)/g)
LEP (Spain)	Long-term value: 10 mg/m <sup>3</sup> e
TWA (Italy)	Long-term value: 10 mg/m <sup>3</sup> (i)
VLE (Portugal)	Long-term value: 10 mg/m <sup>3</sup> Fração inalável; Sintomas nasais
<b>CAS: 65997-15-1 cement portland, grey</b>	
AGW (Germany)	Long-term value: 5 E mg/m <sup>3</sup> DFG
LEP (Spain)	Long-term value: 4 mg/m <sup>3</sup> fracción respirable: e, d
TWA (Italy)	Long-term value: 1 mg/m <sup>3</sup> (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m <sup>3</sup> Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m <sup>3</sup> *hengittyvä pöly, **alveolijae

### 8.2 Exposure controls

#### Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

#### Respiratory protection:

Use suitable respiratory protective device when high concentrations are present.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 5)

**Hand protection**

Protective gloves against chemicals (standard EN 374-1)

The hands must be cleaned from the powder before putting on the gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

**Penetration time of glove material**

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection** Tightly sealed goggles

**Body protection:** Protective work clothing.

### SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties**

**General Information**

**Colour:** According to product specification

**Odour:** Specific type

**Odour threshold:** Not determined.

**Boiling point or initial boiling point and boiling range** Undetermined.

**Flammability** Product is not flammable.

**Lower and upper explosion limit**

**Lower:** Not determined.

**Upper:** Not determined.

**Flash point:** Not applicable

**Auto-ignition temperature:** Not determined.

**Decomposition temperature:** Not determined.

**pH** Alkaline

In water

**Viscosity:**

**Kinematic viscosity** Not determined.

**dynamic:** Not determined.

**Solubility**

**Water:** Miscible

**Partition coefficient n-octanol/water (log value)** Not determined.

**Vapour pressure:** Not applicable.

**Density and/or relative density**

**Density at 20 °C:** 1.4-1.6 g/cm<sup>3</sup>

**Vapour density** Not applicable.

**Particle characteristics**

See section 3.

**9.2 Other information**

No further relevant information available.

**Appearance:**

**Form:** Powder

**Important information on protection of health and environment, and on safety.**

**Explosive properties:** Product does not present an explosion hazard.

(Contd. on page 7)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 6)

**Minimum ignition energy**

**Solvent content:**

**Organic solvents:** 0.0 %

**EU-VOC (g/L)**

**Solids content:** 100 %

**Change in condition**

**Softening point/range**

**Oxidising properties** Not determined.

**Evaporation rate** Not applicable.

**Information with regard to physical hazard classes**

**Explosives** Void

**Flammable gases** Void

**Aerosols** Void

**Oxidising gases** Void

**Gases under pressure** Void

**Flammable liquids** Void

**Flammable solids** Void

**Self-reactive substances and mixtures** Void

**Pyrophoric liquids** Void

**Pyrophoric solids** Void

**Self-heating substances and mixtures** Void

**Substances and mixtures, which emit flammable gases in contact with water** Void

**Oxidising liquids** Void

**Oxidising solids** Void

**Organic peroxides** Void

**Corrosive to metals** Void

**Desensitised explosives** Void

**SECTION 10: Stability and reactivity**

**10.1 Reactivity** When mixed with water the product hardens forming a stable non-reactive mass.

**10.2 Chemical stability** Stable at recommended storage conditions

**10.3 Possibility of hazardous reactions** No dangerous reactions known

**10.4 Conditions to avoid**

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

**10.5 Incompatible materials:** Acids, ammonium salts, aluminum, non-precious metals.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 7)

**LD/LC50 values relevant for classification:**

Components	Type	Value	Species
<b>CAS: 65997-16-2 Cement, alumina, chemicals</b>			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
<b>CAS: 471-34-1 Calcium Carbonate</b>			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
<b>CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO<sub>4</sub> x n H<sub>2</sub>O (n = 0; 1/2; 2)</b>			
Oral	LD50	>2,000 mg/kg	(Rat)
<b>CAS: 65997-15-1 cement portland, grey</b>			
Dermal	LD50	>2,000 mg/kg	(Rabbit)

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation** Causes serious eye damage.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**
**Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

**12.1 Toxicity**
**Aquatic toxicity:** Not classified as harmful to aquatic life

Type of test	Effective concentration	Method	Assessment
<b>CAS: 65997-16-2 Cement, alumina, chemicals</b>			
LC50/96h	100 mg/l	(Fish)	
EC50/24h	6.4 mg/l	(aquatic invertebrates)	
EC50/48h	5.4 mg/l	(aquatic invertebrates)	
EC50/72h	3.6 mg/l	(aquatic algae and cyanobacteria)	
NOEC (72h)	2.6 mg/l	(aquatic algae and cyanobacteria)	
NOEC (48h)	3.4 mg/l	(aquatic invertebrates)	
<b>CAS: 471-34-1 Calcium Carbonate</b>			
EC50/72h	14 mg/l	(Algae)	
<b>CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO<sub>4</sub> x n H<sub>2</sub>O (n = 0; 1/2; 2)</b>			
LC50/48h	79-1,970 mg/l	(aquatic invertebrates)	
LC50/96h	79-2,980 mg/l	(Fish)	
EC50/72h	>79 mg/l	(aquatic algae and cyanobacteria)	

(Contd. on page 9)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 8)

**12.2 Persistence and degradability** The product is not biodegradable.

**12.3 Bioaccumulative potential** Does not accumulate in organisms

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects** No further relevant information available.

**Remark:**

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

**Behaviour in sewage processing plants:**

Type of test / Effective concentration / Method / Assessment	
<b>CAS: 65997-16-2 Cement, alumina, chemicals</b>	
EC 50 (3h)	1,000 mg/l (microorganisms)
<b>CAS: 471-34-1 Calcium Carbonate</b>	
EC 50 (3h)	1,000 mg/l (microorganisms)
<b>CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO<sub>4</sub> x n H<sub>2</sub>O (n = 0; 1/2; 2)</b>	
EC 50 (3h)	>1,000 mg/l (microorganisms)

**Additional ecological information:**

**General notes:**

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**

**Recommendation**

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

**Waste disposal key:**

The classification in a waste code according to the european waste catalogue (EWC) is to be made in accordance with the regional responsible for waste disposal

European waste catalogue	
17 01 01	concrete
16 03 03*	inorganic wastes containing hazardous substances
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**Recommended cleaning agent:** Thoroughly shake out sacks.

EUG

(Contd. on page 10)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 9)

### SECTION 14: Transport information

<b>14.1 UN number or ID number</b> ADR, ADN, IMDG, IATA	Void
<b>14.2 UN proper shipping name</b> ADR, ADN, IMDG, IATA	Void
<b>14.3 Transport hazard class(es)</b> ADR, ADN, IMDG, IATA Class	Void
<b>14.4 Packing group</b> ADR, IMDG, IATA	Void
<b>14.5 Environmental hazards:</b>	Not applicable.
<b>14.6 Special precautions for user</b>	Not applicable.
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
<b>Transport/Additional information:</b>	Not dangerous according to the above specifications.
<b>UN "Model Regulation":</b>	Void

### SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10)

**Labelling according to Regulation (EC) No 1272/2008** cf. section 2

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**REGULATION (EC) No 1907/2006 ANNEX XVII**

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

Conditions of restriction: 47

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**REGULATION (EU) 2019/1148**

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

(Contd. on page 11)

**Safety Data Sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 10)

**Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

**Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

**Relevant phrases**

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

**Classification according to Regulation (EC) No 1272/2008**

Skin corrosion/irritation  
Serious eye damage/irritation

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Department issuing SDS:**

Saint-Gobain Finland Oy / Weber

QEHS

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

**Contact:**

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 520

**Version number of previous version: 2**

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 12)

**Safety Data Sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.09.2024

Version number 3 (replaces version 2)

Revision: 03.09.2024

**Trade name: weberfloor 4660N Marine Elastic**

(Contd. of page 11)

PBT: Persistent, Bioaccumulative and Toxic  
SVHC: Substances of Very High Concern (REACH regulation)  
vPvB: very Persistent and very Bioaccumulative  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

**\* Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG