

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31, as amended
by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: weber PL Quick plaster

Safety data sheet no.: 358P0941

UFI: U7Y3-18G9-EC9U-S8S8

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

1.4 Emergency telephone number:

0800 147 111 (toll-free)

09 471 977 (standard rate)

Finnish Poison Information Centre

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

Cement, alumina, chemicals

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

(Contd. on page 2)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended
by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

(Contd. of page 1)

H335 May cause respiratory irritation.

Precautionary statements

P102 Keep out of reach of children.

P261 Avoid breathing dust.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Ready-mixed mortar with Portland cement

Dangerous components:

CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	25-50%
CAS: 471-34-1 EINECS: 207-439-9 Reg.nr.: 01-2119486795-18-xxxx	Calcium carbonate substance with a Community workplace exposure limit	25-50%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 % substance with a Community workplace exposure limit	10-25%
CAS: 65997-16-2	Cement, alumina, chemicals ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315	≥3-<5%

SVHC Void

Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard statements refer to section 16.

EUG

(Contd. on page 3)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31, as amended
by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Supply fresh air and to be sure call for a doctor.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Use methods suitable to surrounding conditions.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

No special measures required.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

(Contd. on page 4)

EUG

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended
by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

(Contd. of page 3)

Avoid contact with skin and eyes.
 Ensure good ventilation/exhaustion at the workplace.
 Provide suction extractors if dust is formed.
 Apply the product according to the instructions for use.
 Products must be stored in their original packaging, protected from the effects of weather and soil moisture.
 Packaging must remain undamaged to prevent the product from leaking into the environment.
 When opening the packaging, avoid spillage of the product.
 Collect water from cleaning of tools or other equipment for reuse or disposal according to local regulations. Do not dispose cleaning water into the environment or stormwater drains.
Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: Store in dry conditions.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 471-34-1 Calcium carbonate		
Oral	Derived No Effect Level	6.1 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	6.36 mg/m ³ (worker local long term value)
		1.06 mg/m ³ (consumer local long term value)
CAS: 65997-16-2 Cement, alumina, chemicals		
Inhalative	Derived No Effect Level	2.5 mg/m ³ (worker systemic long term value)
		5 mg/m ³ (worker systemic short term value)
PNECs		
CAS: 65997-16-2 Cement, alumina, chemicals		
Predicted No-Effect Concentration	260 mg/l (fresh water rating factor)	
CAS No. / Designation of material / % / Type / Value / Unit		
CAS: 14808-60-7 Silicon dioxide (Quartz sand)		
BOELV (European Union)	Long-term value: 0.1* mg/m ³ *respirable fraction	
MAK (Germany)	alveolengängige Fraktion	
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m ³	
	Long-term value: 0.3* 0.1** mg/m ³ *total, **total, respirabel: EK	
LEP (Spain)	Long-term value: 0.05 mg/m ³ *Fracción resp:n,d,y	

(Contd. on page 5)

Safety Data Sheet
 according to Regulation (EC) No 1907/2006, Article 31, as amended
 by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

(Contd. of page 4)

TWA (Italy)	Long-term value: 0.025 mg/m ³ A2, (j)
VLE (Portugal)	Long-term value: 0.025 mg/m ³ Resp.;A2; fibrose pulmonar; cancro do pulmão
OEL (Sweden)	Long-term value: 0.1 mg/m ³ C, M, respirabel fraktion
HTP (Finland)	Long-term value: 0.05 0.1* mg/m ³ alveolijae;*sitova arvo 113/24, pöly
CAS: 471-34-1 Calcium carbonate	
LEP (Spain)	Long-term value: 10 mg/m ³
TWA (Italy)	Long-term value: (10) mg/m ³ (e)
VLE (Portugal)	Long-term value: (10) mg/m ³ (Irritação)
CAS: 65997-15-1 cement portland, grey	
AGW (Germany)	Long-term value: 5 E mg/m ³ DFG
LEP (Spain)	Long-term value: 4 mg/m ³ fracción respirable: e, d
TWA (Italy)	Long-term value: 1 mg/m ³ (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m ³ Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m ³ *hengittyvä pöly, **alveolijae

8.2 Exposure controls**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Wear a disposable half-mask dust filter in accordance with standard EN149.

Filter P3.

Hand protection

Protective gloves against chemicals (standard EN 374-1)

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Check protective gloves prior to each use for their proper condition.

Material of gloves Nitrile impregnated cotton gloves complying with the standard EN 374-1.

(Contd. on page 6)

EUG

Safety Data Sheet
 according to Regulation (EC) No 1907/2006, Article 31, as amended
 by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

(Contd. of page 5)

Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Protective eyewear (standard EN 166)

Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Solid.
Colour:	Grey
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	Undetermined.
Flammability	Product is not flammable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH	12 - 13 In water
Viscosity:	
Kinematic viscosity	Not applicable.
dynamic:	Not applicable.
Solubility	
Water:	Insoluble
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not applicable.
Density and/or relative density	
Density:	Not applicable.
Relative density	Not determined.
Vapour density	Not applicable.
Particle characteristics	See section 3.

9.2 Other information

Appearance:

Form: Powder

Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

(Contd. on page 7)

Safety Data Sheet
 according to Regulation (EC) No 1907/2006, Article 31, as amended
 by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

(Contd. of page 6)

Minimum ignition energy	
Solvent content:	
Organic solvents:	0.0 %
EU-VOC (%)	0,00 %
EU-VOC (g/L)	
Solids content:	100.0 %
Change in condition	
Softening point/range	
Oxidising properties	Not determined.
Evaporation rate	Not applicable.

Information with regard to physical hazard

classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity** When mixed with water the product hardens forming a stable non-reactive mass.
- 10.2 Chemical stability** Stable at recommended storage conditions
- 10.3 Possibility of hazardous reactions** No dangerous reactions known
- 10.4 Conditions to avoid**
Avoid water ingress/moisture during storage (the product will react with moisture and harden).
- 10.5 Incompatible materials:** Acids, ammonium salts, aluminum, non-precious metals.
- 10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety Data Sheet
 according to Regulation (EC) No 1907/2006, Article 31, as amended
 by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

(Contd. of page 7)

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 471-34-1 Calcium carbonate			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
CAS: 65997-15-1 cement portland, grey			
Dermal	LD50	>2,000 mg/kg	(Rabbit)
CAS: 65997-16-2 Cement, alumina, chemicals			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test / Effective concentration / Method / Assessment	
CAS: 471-34-1 Calcium carbonate	
EC50/72h	14 mg/l (Algae)
CAS: 65997-16-2 Cement, alumina, chemicals	
LC50/96h	100 mg/l (Fish)
EC50/24h	6.4 mg/l (aquatic invertebrates)
EC50/48h	5.4 mg/l (aquatic invertebrates)
EC50/72h	3.6 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	2.6 mg/l (aquatic algae and cyanobacteria)
NOEC (48h)	3.4 mg/l (aquatic invertebrates)

12.2 Persistence and degradability The product is not biodegradable.

12.3 Bioaccumulative potential Does not accumulate in organisms

12.4 Mobility in soil No further relevant information available.

(Contd. on page 9)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended
by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

(Contd. of page 8)

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment	
CAS: 471-34-1 Calcium carbonate	
EC 50 (3h)	1,000 mg/l (microorganisms)
CAS: 65997-16-2 Cement, alumina, chemicals	
EC 50 (3h)	1,000 mg/l (microorganisms)

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

Follow the producers use and disposal instructions to avoid the releases to the environment.

When cleaning tools: remove product residues from the mixing and application tools before cleaning them with water.

Cleaning with a high-pressure cleaner is not recommended, as this could result in the release of the product to the environment, which must be avoided.

Process mortar residues to let them harden, before returning the residues to recycling or disposing them of in accordance with applicable requirements.

Cleaning of silos and bulk trucks must be done according to national regulations to avoid discharged of product or wastewater into the environment.

European waste catalogue	
17 01 01	concrete
16 03 03*	inorganic wastes containing hazardous substances
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 10)

Safety Data Sheet
 according to Regulation (EC) No 1907/2006, Article 31, as amended
 by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

Recommended cleaning agent: Thoroughly shake out sacks.

(Contd. of page 9)

SECTION 14: Transport information

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

This product is subject to the Regulation (EU) 2023/2055 amending REACH Annex XVII 'Restriction List' as regards Synthetic Polymer Microparticles (Entry no.78 on the List).

Portland cement clinker is exempted from registration under the REACH regulation (Article 2(7)(b) and Annex V point 10)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EU) 2017/852 on mercury (Annex I)

None of the ingredients is listed.

REGULATION (EU) 2019/1021 on persistent organic pollutants (POP)

None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

(Contd. on page 11)

Safety Data Sheet
 according to Regulation (EC) No 1907/2006, Article 31, as amended
 by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

(Contd. of page 10)

Conditions of restriction: 47

Regulation (EU) No 649/2012

None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

REGULATION (EU) 2024/590 on substances that deplete the ozone layer

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation

Serious eye damage/irritation

Specific target organ toxicity (single exposure)

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS:

Saint-Gobain Finland Oy / Weber

QEHS

P.O.Box 70 (Strömberginkuja 2)

(Contd. on page 12)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended
by Regulation (EU) 2020/878.

Printing date 10.10.2025

Version number 4 (replaces version 3)

Revision: 10.10.2025

Trade name: weber PL Quick plaster

(Contd. of page 11)

FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 520

Version number of previous version: 3

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.