

# GYPROC J JOINT FILLER



- Good workability properties
- Excellent filling capacity
- The product is a declared item in the Supply Chain Declaration Portal (SCDP) for New Buildings generation 4.

## ABOUT THIS PRODUCT

Ready-mixed, highly filling filler for jointing plasterboard.

## AREA OF USE

For joint and over-leveling on most surfaces such as plaster, concrete and fiberglass fabric.

## SUBSTRATE

Plasterboards.

## TO KNOW BEFORE APPLYING

In case of doubt, please contact Weber technical support.

## WORK INSTRUCTIONS

Gyproc J is applied to the joint with a trowel so that the filler fills the edge thinning. The joint tape is pressed into

## PRODUCT SPECIFICATION

Material consumption	approx. 0.3 l/meter of seam
Application temperature	During the work phase, the temperature of the substrate, screed and room must be above +5 °C.
Drying time	The drying time depends on the base material, layer thickness, temperature, air humidity, etc.
Binder	Copolymer latex
Aggregate	White dolomite and lightweight filler, maximum grain size 0.15 mm
Exposure class	RL 01..04
Color	Beige
Storage conditions	Shelf life 12 months from the date of manufacture (unopened packaging, protected from frost and direct sunlight)
Package	10 liter container
GTIN-codes	6415910055622 (10 l)
Certifications	CE, M1

the filler with a steel trowel and the filler oozing from under the tape is smoothed over the tape. When the filler has dried, the joints are finished by sanding using sandpaper no. 180 - 220.

## DISCLAIMER

As there are different conditions at every opportunity, Weber can not be held responsible for anything other than the information provided under the heading "Product Specification". Examples of information and circumstances, which are outside Saint-Gobain (whether specifically stated or not) include storage, construction, processing, interoperability with other products, workmanship and local conditions.