

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **weber 772 Elastic acrylic paint**

Safety data sheet no.: 358P0139

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

1.4 Emergency telephone number:

0800 147 111 (toll-free)

09 471 977 (standard rate)

Finnish Poison Information Centre

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS07

Signal word Warning**Hazard-determining components of labelling:**

1,2-benzisothiazol-3(2H)-one

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P102 Keep out of reach of children.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

(Contd. on page 2)

-EUG-

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 1)

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Information according to the Biocidal Products Regulation (EU) 528/2012: this product contains biocidal products. Active substance: 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: Plastic dispersion

Dangerous components:

CAS: 1317-65-3 EINECS: 215-279-6 Reg.nr.: 01-2119486795-18-xxxx	calcium carbonate substance with a Community workplace exposure limit	25-50%
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	titanium dioxide substance with a Community workplace exposure limit	5-10%
CAS: 112-34-5 EINECS: 203-961-6 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44-xxxx	2-(2-butoxyethoxy)ethanol ⚠ Eye Irrit. 2, H319	1-2%

(Contd. on page 3)

-EUG-

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6	1,2-benzisothiazol-3(2H)-one ☠ Acute Tox. 2, H330; ☠ Eye Dam. 1, H318; ☠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); ☠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1A, H317 ATE: LD50 oral: 450 mg/kg LC50/4 h inhalative: 0.21 mg/l Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.036 %	(Contd. of page 2) ≥0.036-<0.1%
CAS: 55965-84-9 Index number: 613-167-00-5	reaction mass of 5-chloro-2- methyl-2H- isothiazol-3-one [EC no. 247-500-7] and 2- methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1) ☠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; ☠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ☠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ☠ Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.0015-<0.0025%

SVHC Void

Additional information

(CAS:13463-67-7) Titanium dioxide

Note 10 of CLP classification: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Never administer anything by mouth to an unconscious person.

If unconscious, place the patient in a stable side position and consult a doctor

After inhalation Seek medical treatment in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse immediately and abundantly with water. Seek medical attention, if pain or redness persists.

Remove contact lenses, if possible. Continue rinsing

Call a doctor immediately.

After swallowing Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)

EUG

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 3)

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

When water is vaporized, generation of toxic gases can not be excluded, e.g.:

Carbon monoxide (CO)

Nitrogen oxides (NO_x)

Carbon dioxide (CO₂)

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Wear protective clothing.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

No special measures required.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from freezing.

(Contd. on page 5)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 4)

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 1317-65-3 calcium carbonate		
Oral	Derived No Effect Level	6.1 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	6.36 mg/m ³ (worker local long term value) 1.06 mg/m ³ (consumer local long term value)
CAS: 13463-67-7 titanium dioxide		
Inhalative	Derived No Effect Level	1.25 mg/m ³ (worker local long term value) 0.21 mg/m ³ (consumer local long term value)
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	Derived No Effect Level	6.25 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	101.2 mg/m ³ (worker local short term value) 67.5 mg/m ³ (worker local long term value)
CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one		
Dermal	Derived No Effect Level	0.966 mg/kgxday (worker systemic long term value) 0.345 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	6.81 mg/m ³ (worker systemic long term value) 1.2 mg/m ³ (consumer systemic long term value)
CAS: 55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)		
Oral	Derived No Effect Level	0.09 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	0.02 mg/m ³ (worker local long term value) 0.02 mg/m ³ (consumer local long term value)
PNECs		
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol		
Predicted No-Effect Concentration		0.32 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration		0.11 mg/l (sea water rating factor) 1.1 mg/l (fresh water rating factor)
CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one		
Predicted No-Effect Concentration		3 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration		0.000403 mg/l (sea water rating factor) 0.00403 mg/l (fresh water rating factor)
CAS: 55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)		
Predicted No-Effect Concentration		0.01 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration		0.00339 mg/l (sea water rating factor) 0.00339 mg/l (fresh water rating factor)

(Contd. on page 6)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 5)

CAS No. / Designation of material / % / Type / Value / Unit	
CAS: 1317-65-3 calcium carbonate	
TWA (Italy)	Long-term value: 10 mg/m ³ (e)
CAS: 13463-67-7 titanium dioxide	
AGW (Germany)	Long-term value: 1.25* 10** mg/m ³ 2(II);*alveolengängig**einatembare; AGS, DFG, Y
GV (Denmark)	Short-term value: 12 mg/m ³ Long-term value: 6 mg/m ³ K, som Ti
LEP (Spain)	Long-term value: 10 mg/m ³
TWA (Italy)	Long-term value: 10 mg/m ³ A4
VLE (Portugal)	Long-term value: 10 mg/m ³ A4; Irritação do TRI
OEL (Sweden)	Long-term value: 5 mg/m ³ totaldamm
CAS: 57-55-6 1,2-Propandiol	
MAK (Germany)	als Dampf und Aerosol;vgl.Abschn.IIb und Xc
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol	
IOELV (European Union)	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
AGW (Germany)	Long-term value: 67 mg/m ³ , 10 ppm 1.5(I);EU, DFG, Y, 11
GV (Denmark)	Short-term value: 101 mg/m ³ , 15 ppm Long-term value: 68 mg/m ³ , 10 ppm E
LEP (Spain)	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm VLI, r
VL (Italy)	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
VLE (Portugal)	Long-term value: 10 ppm efeitos hematológicos, no fígado, nos rins
OEL (Sweden)	Short-term value: 101 mg/m ³ , 15 ppm Long-term value: 68 mg/m ³ , 10 ppm
HTP (Finland)	Long-term value: 68 mg/m ³ , 10 ppm
CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one	
MAK (Germany)	vgl.Abschn.IIb und Xc
CAS: 55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)	
MAK (Germany)	Long-term value: 0.2E mg/m ³ vgl.Abschn.Xc

(Contd. on page 7)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 6)

8.2 Exposure controls

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Use skin protection cream for skin protection.

Do not eat, drink, smoke or sniff while working.

Respiratory protection: Not necessary if room is well-ventilated.

Hand protection

Protective gloves against chemicals (standard EN 374-1)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour:	Various colours
Odour:	Mild
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	Undetermined.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH at 20 °C	7-8
Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water:	Partly miscible

(Contd. on page 8)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 7)

Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	1.35 g/cm ³ (DIN 51757)
Vapour density	Not determined.
9.2 Other information	No further relevant information available.
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Explosive properties:	Product does not present an explosion hazard.
Minimum ignition energy	
Solvent content:	
Organic solvents:	0.0 %
EU-VOC (%)	1.8866 %
EU-VOC (g/L)	25.4691 g/l
Change in condition	
Softening point/range	
Oxidising properties	Not determined.
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

10.3 Possibility of hazardous reactions

Contact with aliphatic amines results in an irreversible polymerisation with considerable thermic development.

(Contd. on page 9)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 8)

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 1317-65-3 calcium carbonate			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
Polyacrylate			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
CAS: 13463-67-7 titanium dioxide			
Oral	LD50	>5,000 mg/kg	(Rat)
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol			
Oral	LD50	>2,000 mg/kg	(Mouse)
Dermal	LD50	2,764 mg/kg	(Rabbit)
CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one			
Oral	LD50	450 mg/kg	(ATE)
Dermal	LD50	>2,000 mg/kg	(Rat)
CAS: 55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)			
Oral	LD50	457 mg/kg	(Rat)
Dermal	LD50	660 mg/kg	(Rabbit)
Inhalative	LC50/4 h	2.36 mg/l	(Rat)

Primary irritant effect:
Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

EUG

(Contd. on page 10)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 9)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test / Effective concentration / Method / Assessment

CAS: 1317-65-3 calcium carbonate

LC50/96h	>100 mg/l (Fish)
EC50/48h	>100 mg/l (aquatic invertebrates)
EC50/72h	>14 mg/l (aquatic algae and cyanobacteria)

Polyacrylate

LC50/96h	>1,000 mg/l (Fish)
EC50/48h	>1,000 mg/l (Daphnia magna)

CAS: 13463-67-7 titanium dioxide

LC50/72h	1 mg/l (Fish)
LC50/48h	>100 mg/l (aquatic invertebrates)
LC50/96h	>100 mg/l (Fish)
EC50/48h	>100 mg/l (aquatic invertebrates)
EC50/72h	>100 mg/l (Algae)
NOEC (72h)	≥10 mg/l (aquatic algae and cyanobacteria)
NOEC (96h)	≥1 mg/l (aquatic plants other than algae)
NOEC (21d)	≥100 mg/l (aquatic invertebrates)
NOEC (28d)	≥100 mg/l (aquatic invertebrates)
	≥0.07 mg/l (Fish)

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

LC50/48h	1,000-2,209 mg/l (aquatic invertebrates)
LC50/96h	1,300 mg/l (Fish)
EC50/24h	2,850-3,200 mg/l (aquatic invertebrates)
EC50/48h	>100 mg/l (aquatic invertebrates)
EC50/96h	>100 mg/l (aquatic algae and cyanobacteria)
EC50/72h	1,101 mg/l (aquatic algae and cyanobacteria)
EC 10/18h	1,170 mg/l (microorganisms)

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

LC50/96h	2.15-22 mg/l (Fish)
EC50/48h	2.9 mg/l (aquatic invertebrates)
EC50/72h	0.07-0.15 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	0.0403-0.055 mg/l (aquatic algae and cyanobacteria)

CAS: 55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

LC50/48h	0.18 mg/l (Daphnia magna)
LC50/96h	0.282 mg/l (Daphnia magna)
	0.19-0.3 mg/l (Fish)
EC50/24h	0.109 mg/l (Daphnia magna)

(Contd. on page 11)

EUG

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 10)

EC50/48h	0.0107 mg/l (aquatic algae and cyanobacteria)
	0.16 mg/l (Daphnia magna)
	0.0181-0.0371 mg/l (aquatic algae and cyanobacteria)
EC50/96h	0.0357 mg/l (aquatic algae and cyanobacteria)
EC50/72h	0.0063-0.0273 mg/l (aquatic algae and cyanobacteria)
NOEC (14d)	0.035 mg/l (Daphnia magna)
NOEC (21d)	0.011-1.05 mg/l (Daphnia magna)
NOEC (28d)	0.098 mg/l (Fish)

12.2 Persistence and degradability No further relevant information available.

Method	
CAS: 1317-65-3 calcium carbonate	
Biod. (28 days)	>90 %
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol	
Biod. (28 days)	>80 %

Other information: The product is not easily biodegradable.

12.3 Bioaccumulative potential	
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol	
EBAB	1 log Pow
CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one	
EBAB	0.7 log Pow
CAS: 55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)	
EBAB	0.75 log Pow

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Remark: The product contains substances which causes severe clouding in water

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment	
CAS: 1317-65-3 calcium carbonate	
EC 50 (3h)	>1,000 mg/l (microorganisms)
CAS: 13463-67-7 titanium dioxide	
EC 50 (3h)	1,000 mg/l (microorganisms)
CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one	
EC 50 (3h)	12.8-24 mg/l (microorganisms)
CAS: 55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)	
EC 50 (3h)	4.5 mg/l (microorganisms)

(Contd. on page 12)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 11)

Additional ecological information:**General notes:** Do not allow product to reach ground water, water course or sewage system.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation** Hand over to hazardous waste disposers.**European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP13	Sensitising

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Non contaminated packagings may be recycled.

SECTION 14: Transport information

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

(Contd. on page 13)

EUG

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 12)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008

Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--------------------	--

(Contd. on page 14)

EUG

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.10.2024

Version number 18 (replaces version 17)

Revision: 17.10.2024

Trade name: weber 772 Elastic acrylic paint

(Contd. of page 13)

Department issuing SDS:

Saint-Gobain Finland Oy / Weber

QEHS

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 520

Version number of previous version: 17**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.