

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: weberfloor 4736, comp. A

Safety data sheet no.: 358P0550-a

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy coating

Sealing

Epoxy resin

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

1.4 Emergency telephone number:

0800 147 111 (toll-free)

09 471 977 (standard rate)

Finnish Poison Information Centre

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

4-tert-Butylphenylglycidylether

(Contd. on page 2)

EUG

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 1)

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Does not contain PBT substances.**vPvB:** Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with non hazardous additions.**Dangerous components:**

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-xxxx	2, 2' - [(1 - m e t h y l e t h y l i d e n e) b i s (4 , 1 - p h e n y l e n e o x y m e t h y l e n e)] b i s o x i r a n e ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	50-100%
CAS: 3101-60-8 EINECS: 221-453-2 Reg.nr.: 01-2119959496-20-xxxx	4-tert-Butylphenylglycidylether ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-<10%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22-xxxx	oxirane, mono[(C12-14-alkyloxy)methyl] derivs ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-<10%

SVHC Void**Additional information** For the wording of the listed hazard statements refer to section 16.

EUG

(Contd. on page 3)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Never administer anything by mouth to an unconscious person.

If unconscious, place the patient in a stable side position and consult a doctor

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Use fire extinguishing methods suitable to surrounding conditions.

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents Water with full jet

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Carbon monoxide (CO)

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

6.2 Environmental precautions:

The product must not get into watercourses or into the soil.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

EUG

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 3)

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Prevent formation of aerosols.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Store away from oxidising agents.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Recommended storage temperature: 5-30°C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Oral	Derived No Effect Level	0.5 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	0.75 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	0.0893 mg/kgxday (consumer systemic long term value)
		4.93 mg/m ³ (worker systemic long term value)
		0.87 mg/m ³ (consumer systemic long term value)

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Oral	Derived No Effect Level	0.05 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	0.75 mg/kgxday (worker systemic long term value)
		0.089 mg/kgxday (consumer systemic long term value)

(Contd. on page 5)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 4)

Inhalative	Derived No Effect Level	0.49 mg/m ³ (worker systemic long term value) 0.087 mg/m ³ (consumer systemic long term value)
------------	-------------------------	---

PNECs**CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane**

Predicted No-Effect Concentration 0.065 mg/kgxdwt (earth rating factor)

Predicted No-Effect Concentration 0.0006 mg/l (sea water rating factor)

0.006 mg/l (fresh water rating factor)

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Predicted No-Effect Concentration 20 mg/kgxdwt (earth rating factor)

Predicted No-Effect Concentration 0.112 mg/l (sea water rating factor)

1.12 mg/l (fresh water rating factor)

CAS No. / Designation of material / % / Type / Value / Unit**CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane**

MAK (Germany) | vgl. Abschn. IIb

CAS: 3101-60-8 4-tert-Butylphenylglycidylether

MAK (Germany) | als Dampf und Aerosol, vgl. Abschn. IV

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Respiratory protection:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A2

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

Recommended thickness of the material: ≥ (Butyl) 0.7mm; (NBR) 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several

(Contd. on page 6)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 5)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Breakthrough time: > 480 min

Value for the permeation: Level ≤ 6

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour:	Light brown
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	Undetermined.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	> 100 °C
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH	Not applicable.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic at 20 °C:	1.400 mPas (DIN EN ISO 3219)
Solubility	
Water:	Emulsifiable
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	1.12 g/cm ³ (DIN EN ISO 2811-2)
Bulk density:	Not applicable.
Vapour density	Not determined.
Particle characteristics	See section 3.

9.2 Other information

Appearance:	None.
Form:	Pasty
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.
EU-VOC (%)	0.0000 %

(Contd. on page 7)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 6)

EU-VOC (g/L)	0.0000 g/l
Change in condition	
Softening point/range	
Oxidising properties	Not determined.
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / Conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Exothermic polymerisation.

Reacts with alcohols, amines, aqueous acids and alkalis

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Irritant gases/vapours

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 7)

LD/LC50 values relevant for classification:

Components	/	Type	/	Value	/	Species
CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane						
Oral	LD50	>15,000 mg/kg	(Rat)			
Dermal	LD50	>23,000 mg/kg	(Rat)			
CAS: 3101-60-8 4-tert-Butylphenylglycidylether						
Oral	LD50	>10,000 mg/kg	(Rat)			
Dermal	LD50	>4,600 mg/kg	(Rat)			
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs						
Oral	LD50	>2,000 mg/kg	(Rat)			
Dermal	LD50	>4,000 mg/kg	(Rabbit)			

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.

Type of test / Effective concentration / Method / Assessment	
CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	
LC50/96h	2 mg/l (Fish)
EC50/48h	1.8 mg/l (Daphnia magna)
EC50/72h	>11 mg/l (Algae)
NOEC (72h)	4.2 mg/l (Algae)
NOEC (21d)	0.3 mg/l (Daphnia magna)
CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs	
IC50/72h	843.75 mg/l (aquatic algae and cyanobacteria)
LC50/96h	>100 mg/l (Fish)
EC50/48h	7.2 mg/l (aquatic invertebrates)
EC50/72h	843.75 mg/l (aquatic algae and cyanobacteria)

(Contd. on page 9)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 8)

NOEC (72h)	500 mg/l (aquatic algae and cyanobacteria)
------------	--

NOEC (21d)	56 mg/l (aquatic invertebrates)
------------	---------------------------------

NOEC (28d)	100 mg/l (microorganisms)
------------	---------------------------

12.2 Persistence and degradability No further relevant information available.

Method

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Biod. (28 days)	>80 %
-----------------	-------

12.3 Bioaccumulative potential

CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EBAB	3.242 log Pow
------	---------------

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

EBAB	3.77 log Pow (-)
------	------------------

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark:

The product contains substances which are toxic to fishes and bacteria.

Toxic for fish

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment
--

CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC 50 (3h)	100 mg/l (microorganisms)
------------	---------------------------

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs
--

EC 50 (3h)	100 mg/l (microorganisms)
------------	---------------------------

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Curing of the product by mixing with the curing component. Cured epoxy resin products are waste that requires no particular supervision and can as a rule be disposed of as commercial waste that is similar to household rubbish.

(Contd. on page 10)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 9)

European waste catalogue

08 04 09* | waste adhesives and sealants containing organic solvents or other hazardous substances

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN3082

14.2 UN proper shipping name

ADR 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)
 IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin), MARINE POLLUTANT
 IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)

14.3 Transport hazard class(es)


ADR



Class 9 (M6) Miscellaneous dangerous substances and articles.

Label 9

IMDG, IATA



Class 9 Miscellaneous dangerous substances and articles.

Label 9

14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant: Yes
 Symbol (fish and tree)

Special marking (ADR): Symbol (fish and tree)

(Contd. on page 11)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 10)

Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Hazard identification number (Kemler code):	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g
Transport category	3
Tunnel restriction code	(-)
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 12)

Safety Data Sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 11)

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation

Serious eye damage/irritation

Skin sensitisation

Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS:

Saint-Gobain Finland Oy / Weber

QEHS

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 520

Version number of previous version: 3

(Contd. on page 13)

Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.10.2024

Version number 4 (replaces version 3)

Revision: 22.03.2022

Trade name: weberfloor 4736, comp. A

(Contd. of page 12)

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

