

**Safety Data Sheet**  
according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name: **weber 1-K Polyurethane elastomer**

Safety data sheet no.: 358P0169

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

The product is intended for industrial or professional use.

**Application of the substance / the mixture**

Construction chemicals

Coating

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:**

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

**1.4 Emergency telephone number:**

0800 147 111 (toll-free)

09 471 977 (standard rate)

Finnish Poison Information Centre

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3            H226 Flammable liquid and vapour.

Acute Tox. 4           H332 Harmful if inhaled.

Skin Sens. 1           H317 May cause an allergic skin reaction.

Aquatic Chronic 3    H412 Harmful to aquatic life with long lasting effects.

**2.2 Label elements**

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**



GHS02    GHS07

**Signal word** Warning

**Hazard-determining components of labelling:**

Aliphatic polyisocyanate

Solvent naphtha (petroleum), light arom.

1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

(Contd. on page 2)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 1)

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate homopolymer, isocyanurate type  
2-ethylhexyl (6-isocyanatoethyl)-carbamate  
hexahydromethylphthalic anhydride  
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate  
hexamethylene diisocyanate

**Hazard statements**

H226 Flammable liquid and vapour.  
H332 Harmful if inhaled.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P260 Do not breathe mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

**Description:** Mixture consisting of the following components.

**Dangerous components:**

CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35-xxxx	Barium Sulfate substance with a Community workplace exposure limit	10-20%
CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335- H336, EUH066	5-10%

(Contd. on page 3)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

		(Contd. of page 2)
CAS: 140921-24-0 ELINCS: 411-700-4 Index number: 616-079-00-5 Reg.nr.: 01-0000015906-63-xxxx 01-2119983489-15-xxxx	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate ⚠ Skin Sens. 1, H317	5-10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336 substance with a Community workplace exposure limit	5-10%
CAS: 1308-38-9 EINECS: 215-160-9 Reg.nr.: 01-2119433951-39-xxxx	Chromium (III) oxide substance with a Community workplace exposure limit	2-5%
CAS: 53880-05-0 EC number: 931-312-3 Reg.nr.: 01-2119488734-24-xxxx	3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate homopolymer, isocyanurate type ⚠ Skin Sens. 1, H317; STOT SE 3, H335	2-5%
CAS: 26488-60-8 EINECS: 247-735-5 Reg.nr.: 01-2120770989-29-xxxx	2-ethylhexyl (6-isocyanatoethyl)-carbamate ⚠ Acute Tox. 3, H331; ⚠ Skin Sens. 1B, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥2.5-<5%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119486773-24-xxxx	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335- H336 Note: H, P, 4 substance with a Community workplace exposure limit	1-2%
CAS: 8002-74-2 EINECS: 232-315-6 Reg.nr.: 01-2119488076-30-xxxx	Paraffin waxes and Hydrocarbon waxes substance with a Community workplace exposure limit	1-2%
CAS: 76977-79-2 EINECS: 278-583-8	Bis(2-ethylhexyl) 1,6-hexan-1,6-diylbiscarbamate ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1, H317	≥0.25-<1%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5 Reg.nr.: 01-2119490408-31-xxxx	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate ⚠ Acute Tox. 3, H331; ⚠ Resp. Sens. 1, H334; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 % substance with a Community workplace exposure limit	≥0.1-<0.25%
<b>SVHC Void</b>		(Contd. on page 4)

**Safety Data Sheet**  
according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer****Additional information** For the wording of the listed hazard statements refer to section 16.

(Contd. of page 3)

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information**

Immediately remove any clothing soiled by the product.

Never administer anything by mouth to an unconscious person.

If unconscious, place the patient in a stable side position and consult a doctor

**After inhalation** Supply fresh air and to be sure call for a doctor.**After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

**After swallowing**

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

**4.2 Most important symptoms and effects, both acute and delayed** Allergic reactions**4.3 Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents**

Alcohol-resistant foam

Fire-extinguishing powder

Carbon dioxide

Water haze

**For safety reasons unsuitable extinguishing agents** Water with full jet**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

**5.3 Advice for firefighters****Protective equipment:** Wear self-contained respiratory protective device.**Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources

**6.2 Environmental precautions:**

The product must not get into watercourses or into the soil.

(Contd. on page 5)

EUG

**Safety Data Sheet**  
 according to Regulation (EC) No 1907/2006, Article 31, as amended  
 by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 4)

Inform respective authorities in case of seepage into water course or sewage system.

**6.3 Methods and material for containment and cleaning up:**

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb with sawdust or other combustible absorbents.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Apply the product according to the instructions for use.

Packaging must remain undamaged to prevent the product from leaking into the environment.

When opening the packaging, avoid spillage of the product.

Collect water from cleaning of tools or other equipment for reuse or disposal according to local regulations. Do not dispose cleaning water into the environment or stormwater drains.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Use explosion-proof apparatus / fittings and spark-proof tools.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage**

**Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

**Information about storage in one common storage facility:** Store away from foodstuffs.

**Further information about storage conditions:**

Protect from heat and direct sunlight.

Store in dry conditions.

Store receptacles in a well ventilated area.

Keep container tightly sealed.

**7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

<b>DNELs</b>		
<b>CAS: 7727-43-7 Barium Sulfate</b>		
Oral	Derived No Effect Level	13,000 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	10 mg/m <sup>3</sup> (worker systemic long term value)
		10 mg/m <sup>3</sup> (consumer systemic long term value)

(Contd. on page 6)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 5)

**CAS: 128601-23-0 Hydrocarbons, C9, aromatics**

Oral	Derived No Effect Level	7.5 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	12.5 mg/kgxday (worker systemic long term value) 7.5 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	151 mg/m <sup>3</sup> (worker systemic long term value) 32 mg/m <sup>3</sup> (consumer systemic long term value)

**CAS: 140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate**

Oral	Derived No Effect Level	12.5 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	140 mg/kgxday (worker systemic long term value) 50 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	49.4 mg/m <sup>3</sup> (worker systemic long term value) 8.7 mg/m <sup>3</sup> (consumer systemic long term value)

**CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

Oral	Derived No Effect Level	36 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	796 mg/kgxday (worker systemic long term value) 320 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	275 mg/m <sup>3</sup> (worker systemic long term value) 33 mg/m <sup>3</sup> (consumer systemic long term value) 550 mg/m <sup>3</sup> (worker local short term value) 33 mg/m <sup>3</sup> (consumer local long term value)

**CAS: 53880-05-0 3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate homopolymer, isocyanurate type**

Inhalative	Derived No Effect Level	0.58 mg/m <sup>3</sup> (worker local short term value) 0.29 mg/m <sup>3</sup> (worker local long term value)
------------	-------------------------	---

**CAS: 26488-60-8 2-ethylhexyl (6-isocyanatoethyl)-carbamate**

Inhalative	Derived No Effect Level	0.011 mg/m <sup>3</sup> (worker local short term value) 0.006 mg/m <sup>3</sup> (worker local long term value)
------------	-------------------------	---

**CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.**

Inhalative	Derived No Effect Level	1.9 mg/m <sup>3</sup> (worker systemic long term value) 0.41 mg/m <sup>3</sup> (consumer systemic long term value)
------------	-------------------------	---

**CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate**

Inhalative	Derived No Effect Level	0.045 mg/m <sup>3</sup> (worker local short term value) 0.045 mg/m <sup>3</sup> (worker local long term value)
------------	-------------------------	---

**PNECs**

**CAS: 7727-43-7 Barium Sulfate**

Predicted No-Effect Concentration	207.7 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	0.115 mg/l (fresh water rating factor)

**CAS: 140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate**

Predicted No-Effect Concentration	140.4 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	0.002 mg/l (sea water rating factor) 0.016 mg/l (fresh water rating factor)

(Contd. on page 7)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 6)

**CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

Predicted No-Effect Concentration	0.29 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	0.064 mg/l (sea water rating factor)
	0.635 mg/l (fresh water rating factor)

**CAS: 26488-60-8 2-ethylhexyl (6-isocyanatohexyl)-carbamate**

Predicted No-Effect Concentration	1.6 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	0.0001 mg/l (sea water rating factor)
	0.001 mg/l (fresh water rating factor)

**CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate**

Predicted No-Effect Concentration	19.8 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	0 mg/l (sea water rating factor)
	0.027 mg/l (fresh water rating factor)

**CAS No. / Designation of material / % / Type / Value / Unit**

**CAS: 7727-43-7 Barium Sulfate**

AGW (Germany)	Long-term value: 1.25* 10** mg/m <sup>3</sup> 2(II);*alveolengängig**einatembare; AGS, DFG, Y
LEP (Spain)	Long-term value: 10 mg/m <sup>3</sup> e
TWA (Italy)	Long-term value: 10 mg/m <sup>3</sup>
VLE (Portugal)	Long-term value: 5 mg/m <sup>3</sup> Fração inalável; Pneumoconiose

**CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

IOELV (European Union)	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm Skin
AGW (Germany)	Long-term value: 270 mg/m <sup>3</sup> , 50 ppm 1(I);DFG, EU, Y
GV (Denmark)	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm EH
LEP (Spain)	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm vía dérmica, VLI
VL (Italy)	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm Cute
OEL (Sweden)	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm H
HTP (Finland)	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 270 mg/m <sup>3</sup> , 50 ppm iho

(Contd. on page 8)

**Safety Data Sheet**  
 according to Regulation (EC) No 1907/2006, Article 31, as amended  
 by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 7)

**CAS: 1308-38-9 Chromium (III) oxide**

IOELV (European Union)	Long-term value: 2 mg/m <sup>3</sup> as Cr
AGW (Germany)	Long-term value: 2 E mg/m <sup>3</sup> 1(I);10, EU
GV (Denmark)	Short-term value: 1.0 mg/m <sup>3</sup> Long-term value: 0.5 mg/m <sup>3</sup> E, som Cr
LEP (Spain)	Long-term value: 2 mg/m <sup>3</sup> VLI, como Cr
VL (Italy)	Long-term value: 0.5 mg/m <sup>3</sup>
VLE (Portugal)	Long-term value: 0.5 mg/m <sup>3</sup> A4; Irrit. TRS e cutânea; em Cr
OEL (Sweden)	Long-term value: 0.5 mg/m <sup>3</sup> som Cr; totaldamm
HTP (Finland)	Long-term value: 0.5 mg/m <sup>3</sup> Cr

**CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.**

MAK (Germany)	Long-term value: 200 mg/m <sup>3</sup> , 50 ppm TRGS 900, Gruppe 3
---------------	---

**CAS: 8002-74-2 Paraffin waxes and Hydrocarbon waxes**

GV (Denmark)	Short-term value: 4 mg/m <sup>3</sup> Long-term value: 2 mg/m <sup>3</sup>
LEP (Spain)	Long-term value: 2 mg/m <sup>3</sup> humos
TWA (Italy)	Long-term value: 2 mg/m <sup>3</sup>
VLE (Portugal)	Long-term value: 2 mg/m <sup>3</sup> Irritação do TRS; Náuseas
HTP (Finland)	Long-term value: 1 mg/m <sup>3</sup>

**CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate**

BOELV (European Union)	Short-term value: 0.012 (0.020)* mg/m <sup>3</sup> Long-term value: 0.006 (0.010)* mg/m <sup>3</sup> as -NCO *until 31.12.2028
AGW (Germany)	Long-term value: 0.006 mg/m <sup>3</sup> 2;gemessen als -NCO; EU, 11, 12, 37, Sah
GV (Denmark)	Short-term value: 0.090 mg/m <sup>3</sup> , 0.01 ppm Long-term value: 0.045 mg/m <sup>3</sup> , 0.005 ppm
LEP (Spain)	Long-term value: 0.046 mg/m <sup>3</sup> , 0.005 ppm Sen, r, véase Capítulo 9
TWA (Italy)	Long-term value: 0.045 mg/m <sup>3</sup> , 0.005 ppm
VLE (Portugal)	Long-term value: 0.005 ppm Sensibilização respiratória
OEL (Sweden)	Short-term value: 0.046 mg/m <sup>3</sup> , 0.005 ppm Long-term value: 0.018 mg/m <sup>3</sup> , 0.002 ppm M, SH, SL

(Contd. on page 9)

**Safety Data Sheet**  
 according to Regulation (EC) No 1907/2006, Article 31, as amended  
 by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 8)

HTP (Finland)

Short-term value: 0.035 mg/m<sup>3</sup>  
NCO

**8.2 Exposure controls**

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Ensure that washing facilities are available at the work place.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

**Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A

**Hand protection**

Protective gloves against chemicals (standard EN 374-1)

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.

**Penetration time of glove material**

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection**

Protective eyewear complying with EN ISO 16321-1:2022

Tightly sealed goggles

**Body protection:** Protective work clothing.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

<b>Physical state</b>	Liquid
<b>Colour:</b>	Coloured
<b>Odour:</b>	Aromatic
<b>Odour threshold:</b>	Not determined
<b>Melting point/freezing point:</b>	Undetermined
<b>Boiling point or initial boiling point and boiling range</b>	150-180 °C
<b>Flammability</b>	Flammable.
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	Not determined
<b>Upper:</b>	Not determined
<b>Flash point:</b>	38 °C
<b>Auto-ignition temperature:</b>	Not determined.
<b>Decomposition temperature:</b>	Not determined
<b>pH</b>	Not applicable.
<b>Viscosity:</b>	
<b>Kinematic viscosity</b>	Not determined.

(Contd. on page 10)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

Trade name: weber 1-K Polyurethane elastomer

(Contd. of page 9)

<b>Kinematic viscosity at 40 °C</b>	2500-8000 mm <sup>2</sup> /s
<b>dynamic:</b>	Not determined.
<b>Solubility</b>	
<b>Water:</b>	Fully miscible
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined
<b>Vapour pressure:</b>	Not determined
<b>Density and/or relative density</b>	
<b>Density:</b>	Not determined
<b>Relative density at 23 °C</b>	1.48-1.58
<b>Bulk density:</b>	Not applicable.
<b>Vapour density</b>	Not determined

### 9.2 Other information

**Appearance:**

**Form:** Liquid

**Important information on protection of health  
and environment, and on safety.**

**Ignition temperature:**

Product is not self-igniting.

**Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**Minimum ignition energy**

**Solvent separation test:**

Not applicable.

**EU-VOC (%)**

16.6000 %

**Change in condition**

**Softening point/range**

**Oxidising properties**

Not determined.

**Evaporation rate**

Not determined

### Information with regard to physical hazard classes

<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Flammable liquid and vapour.
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void

(Contd. on page 11)

EUG

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 10)

Desensitised explosives

Void

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

This product can react with some agents under certain conditions. See the other points in this section

**10.2 Chemical stability** Stable at recommended storage conditions

**10.3 Possibility of hazardous reactions** Flammable

#### 10.4 Conditions to avoid

Keep away from heat sources.

Avoid heat, sparkles, naked flame or other sources of ignition.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Harmful if inhaled.

##### LD/LC50 values relevant for classification:

Components	Type	Value	Species
<b>CAS: 7631-86-9 silicon dioxide, chemically prepared</b>			
Oral	LD50	>5,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rabbit)
<b>CAS: 7727-43-7 Barium Sulfate</b>			
Oral	LD50	>5,000 mg/kg	(Rat)
<b>CAS: 128601-23-0 Hydrocarbons, C9, aromatics</b>			
Oral	LD50	3,492 mg/kg	(Rat)
Dermal	LD50	>3,160 mg/kg	(Rabbit)
<b>CAS: 140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate</b>			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
<b>CAS: 108-65-6 2-methoxy-1-methylethyl acetate</b>			
Oral	LD50	6,190 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
<b>CAS: 1308-38-9 Chromium (III) oxide</b>			
Oral	LD50	>5,000 mg/kg	(Rat)
Inhalative	LC50/4 h	>5.41 mg/l	(Rat)
<b>CAS: 53880-05-0 3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate homopolymer, isocyanurate type</b>			
Oral	LD50	14,000 mg/kg	(Rat)
Inhalative	LC50/4 h	>5 mg/l	(Rat)

(Contd. on page 12)

**Safety Data Sheet**  
 according to Regulation (EC) No 1907/2006, Article 31, as amended  
 by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 11)

<b>CAS: 26488-60-8 2-ethylhexyl (6-isocyanatohexyl)-carbamate</b>		
Oral	LD50	>2,000 mg/kg (Rat)
Inhalative	LC50/4 h	>0.521 mg/l (Rat)
<b>CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.</b>		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)
<b>CAS: 8002-74-2 Paraffin waxes and Hydrocarbon waxes</b>		
Oral	LD50	5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
<b>CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate</b>		
Oral	LD50	4,814 mg/kg (Rat)
Dermal	LD50	7,000 mg/kg (Rat)
Inhalative	LC50/4 h	>31 mg/l (Rat)

**Primary irritant effect:**

**Skin corrosion/irritation** Skin irritation possible due to drying effect.

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:** Harmful to aquatic life with long lasting effects.

Type of test / Effective concentration / Method / Assessment	
<b>CAS: 7631-86-9 silicon dioxide, chemically prepared</b>	
LC50/96h	>5,000 mg/l (Fish)
EC50/48h	>5,000 mg/l (aquatic invertebrates)
EC50/96h	217.576-217.6 mg/l (aquatic algae and cyanobacteria)
EC50/72h	173.1-1,000 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	173.1-1,000 mg/l (aquatic algae and cyanobacteria)
NOEC (48h)	>5,000 mg/l (aquatic invertebrates)
NOEC (21d)	68-250 mg/l (aquatic invertebrates)
<b>CAS: 7727-43-7 Barium Sulfate</b>	
LC50/48h	14.5 mg/l (aquatic invertebrates)

(Contd. on page 13)

**Safety Data Sheet**  
 according to Regulation (EC) No 1907/2006, Article 31, as amended  
 by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 12)

LC50/96h	3.5-174 mg/l (Fish)
EC50/48h	58.8 mg/l (aquatic invertebrates)
EC50/72h	1.15-113 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	1.15-100 mg/l (aquatic algae and cyanobacteria)
NOEC (48h)	58.8 mg/l (aquatic invertebrates)
<b>CAS: 128601-23-0 Hydrocarbons, C9, aromatics</b>	
LC50/96h	9.22 mg/l (Fish)
EC50/48h	6.14 mg/l (aquatic invertebrates)
EC50/72h	0.29-0.42 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	0.07 mg/l (aquatic algae and cyanobacteria)
<b>CAS: 140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate</b>	
LC50/96h	199.2 mg/l (Fish)
LC0/96h	70.7 mg/l (Fish)
EC50/24h	253 mg/l (aquatic invertebrates)
EC50/48h	193 mg/l (aquatic invertebrates)
EC50/72h	29 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	12.5 mg/l (aquatic algae and cyanobacteria)
EC 10	350 mg/l (microorganisms)
<b>CAS: 108-65-6 2-methoxy-1-methylethyl acetate</b>	
LC50/48h	408 mg/l (aquatic invertebrates)
LC50/96h	130 mg/l (Fish)
EC50/48h	373-380 mg/l (aquatic invertebrates)
EC50/96h	>1,000 mg/l (aquatic algae and cyanobacteria)
NOEC (96h)	>1,000 mg/l (aquatic algae and cyanobacteria)
NOEC (14d)	47.5 mg/l (Fish)
NOEC (21d)	>100 mg/l (aquatic invertebrates)
<b>CAS: 1308-38-9 Chromium (III) oxide</b>	
LC50/96h	>10,000 mg/l (Fish)
EC50/48h	>14.1 mg/l (aquatic invertebrates)
EC50/72h	>0.148 mg/l (aquatic algae and cyanobacteria)
NOEC (21d)	>0.014 mg/l (aquatic invertebrates)
<b>CAS: 53880-05-0 3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate homopolymer, isocyanurate type</b>	
EC50/48h	3.36 mg/l (Daphnia magna)
EC50/72h	3.1 mg/l (Algae)
<b>CAS: 26488-60-8 2-ethylhexyl (6-isocyanatoethyl)-carbamate</b>	
EC50/72h	1.002 mg/l (Algae)
NOEC (72h)	0.163 mg/l (Algae)
<b>CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.</b>	
EC50/96h	10 mg/l (Fish)

(Contd. on page 14)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 13)

**CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate**

LC50/96h	208 mg/l (Fish)
EC50/48h	27 mg/l (aquatic invertebrates)
EC50/72h	>70 mg/l (aquatic algae and cyanobacteria)
NOEC (72h)	4.4 mg/l (aquatic algae and cyanobacteria)

**12.2 Persistence and degradability** No further relevant information available.

**Method**

**CAS: 128601-23-0 Hydrocarbons, C9, aromatics**

Biod. (28 days) 78 % (Biodegradation)

**CAS: 140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate**

Biod. (28 days) 43 %

**CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

Biod. (28 days) >80 %

**CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate**

Biod. (28 days) 0 %

**12.3 Bioaccumulative potential**

**CAS: 128601-23-0 Hydrocarbons, C9, aromatics**

EBAB 3.03-4.73 log Pow

**CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

EBAB 1.2 log Pow (Biodegradation)

**CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate**

EBAB 4.75 log Pow (Bioaccumulation)

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects**

**Remark:** The product contains substances which are toxic to fishes and bacteria.

**Behaviour in sewage processing plants:**

**Type of test / Effective concentration / Method / Assessment**

**CAS: 7631-86-9 silicon dioxide, chemically prepared**

EC 50 (3h) 1,000-4,500 mg/l (microorganisms)

**CAS: 7727-43-7 Barium Sulfate**

EC 50 (3h) 622-1,000 mg/l (microorganisms)

**CAS: 140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate**

EC 50 (3h) 1,770 mg/l (microorganisms)

**CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

EC 50 (3h) >1,000 mg/l (microorganisms)

**CAS: 1308-38-9 Chromium (III) oxide**

EC 50 (3h) 1,041-10,000 mg/l (microorganisms)

(Contd. on page 15)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 14)

**CAS: 26488-60-8 2-ethylhexyl (6-isocyanatohexyl)-carbamate**

EC 50 (3h) | 64 mg/l (microorganisms)

**CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate**

EC 50 (3h) | 263 mg/l (microorganisms)

**Additional ecological information:**

**General notes:**

Do not allow product to reach ground water, water course or sewage system.  
Harmful to aquatic organisms

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**

**Recommendation**

Follow the producers use and disposal instructions to avoid the releases to the environment.

Hand over to hazardous waste disposers.

When cleaning tools: remove product residues from the mixing and application tools before cleaning them with water.

Cleaning with a high-pressure cleaner is not recommended, as this could result in the release of the product to the environment, which must be avoided.

**European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP14	Ecotoxic

**Uncleaned packaging:**

**Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

### SECTION 14: Transport information

**14.1 UN number or ID number**

ADR, IMDG, IATA UN1263

**14.2 UN proper shipping name**

ADR 1263 PAINT  
IMDG, IATA PAINT

**14.3 Transport hazard class(es)**

**ADR**



**Class** 3 (F1) Flammable liquids.

(Contd. on page 16)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.


Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 15)

<b>Label</b>	3
<b>IMDG, IATA</b>	
	
<b>Class</b>	3 Flammable liquids.
<b>Label</b>	3
<b>14.4 Packing group ADR, IMDG, IATA</b>	III
<b>14.5 Environmental hazards: Marine pollutant:</b>	No
<b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
<b>Hazard identification number (Kemler code):</b>	30
<b>EMS Number:</b>	F-E, <u>S</u> -E
<b>Stowage Category</b>	A
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable
<b>Transport/Additional information:</b>	
<b>ADR</b>	
<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>Transport category</b>	3
<b>Tunnel restriction code</b>	D/E
<b>IMDG</b>	
<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

This product is subject to the Regulation (EU) 2023/2055 amending REACH Annex XVII 'Restriction List' as regards Synthetic Polymer Microparticles (Entry no.78 on the List).

**Labelling according to Regulation (EC) No 1272/2008** cf. section 2

(Contd. on page 17)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 16)

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**REGULATION (EU) 2017/852 on mercury (Annex I)**

None of the ingredients is listed.

**REGULATION (EU) 2019/1021 on persistent organic pollutants (POP)**

None of the ingredients is listed.

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 74

**Additional information on Entry 78**

The product falls under the microplastics restriction but is derogated under paragraph 5 of Regulation(EU) 2023/2055.

**Regulation (EU) No 649/2012**

None of the ingredients is listed.

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**REGULATION (EU) 2019/1148**

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

**Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

**REGULATION (EU) 2024/590 on substances that deplete the ozone layer**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

**Relevant phrases**

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

(Contd. on page 18)

**Safety Data Sheet**  
 according to Regulation (EC) No 1907/2006, Article 31, as amended  
 by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 17)

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH204 Contains isocyanates. May produce an allergic reaction.

**Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	On basis of test data
Acute toxicity - inhalation Skin sensitisation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Department issuing SDS:**

Saint-Gobain Finland Oy / Weber  
 QEHS  
 P.O.Box 70 (Strömberginkuja 2)  
 FI-00381 Helsinki

**Contact:**

Tel. +358-(0)10-44 22 00  
 Fax +358-(0)10-44 22 520

**Version number of previous version: 2**

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
 ICAO: International Civil Aviation Organisation  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 SVHC: Substances of Very High Concern (REACH regulation)  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 3: Acute toxicity – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Resp. Sens. 1: Respiratory sensitisation – Category 1  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Skin Sens. 1B: Skin sensitisation – Category 1B  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 19)

**Safety Data Sheet**  
according to Regulation (EC) No 1907/2006, Article 31, as amended  
by Regulation (EU) 2020/878.

Printing date 04.05.2026

Version number 3 (replaces version 2)

Revision: 04.05.2026

**Trade name: weber 1-K Polyurethane elastomer**

(Contd. of page 18)

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**\* Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG